

TOSHIBA

SMMS 7
SUPER MODULAR MULTI SYSTEM

The First VRF
FOR
Tropical Climate

"SMMS -7 the senses of cooling"



VRF Air Conditioning for Large Building
Product Catalogue

 **Better Air Solutions**

INDEX

Introduction

Toshiba air conditioning vision	3
7 Senses of smartness	
7 Smart features	4
Product line up	6

7 Smart features

Higher energy efficiency	7
Space saving and light weight	8
Wider ambient operation	9
Environmentally- oriented	9
High reliability	10
Design flexibility	12
Easy installation and maintenance	14
New path of heat exchanger	16
New developed accumulator	17

Outdoor units


Outdoor units line-up	18
Outdoor units specifications	26
Outdoor units external view drawings	28

Indoor units

Indoor units line-up for SMMS-7	32
4-way air discharge cassette type	34
Compact 4-way cassette type	36
2-way air discharge cassette type	38
1-way air discharge cassette type	40
Slim duct type	42
Super slim duct type	44
Concealed duct high static pressure type	46
Concealed duct type	48
Ceiling type	50
High-wall type (series 3)	52
High-wall type (series 7)	53
Floor standing concealed type	54
Floor standing cabinet type	55
Console type	56
Floor standing type	57
Large capacity floor standing duct type	58
Large capacity floor standing direct type	59
DX-COIL Interface	60
Fresh air intake indoor unit type	62
Air-to-Air heat exchanger with DX-coil	64
Air-to-Air heat exchange (stand alone unit)	66
Indoor unit accessories for SMMS-7	68

Remote controllers	70
Building management systems	74
Open network systems	76
Application controls	78
Safety precautions	81

TOSHIBA AIR CONDITIONING VISION



Better Air Solutions

Through our commitment to world-class efficiency, versatile scalability and leading quality, Toshiba Air Conditioning advances leading-edge technologies to find the most forward-thinking solutions possible for your world.



7

Senses

Because understand your real needs, we have in air conditioning, which we have innovately this VRF is cooling optimized for hot and humid

»»» Sense of efficiency

Higher energy efficiency

»»» Sense of care

Environmentally - oriented

»»» Sense of space

Space saving and light weight



»»» Sense of environment

Wider ambient

of smartness

we searched for and finally found 7 senses of smartness developed into the most advance technologies SMMS-7 and temperature.

»»» Sense of convenience

Easy installation and maintenance

»»» Sense of flexibility

Design flexibility

»»» Sense of strength

High reliability




durance
operation

SMMS 7
SUPER MODULAR MULTI SYSTEM

"SMMS-7 the senses of cooling"

Sense of efficiency

Higher energy efficiency



* Note: (L) is high Efficiency model

>>> Sense of space

Space saving and light weight

◀ 20 HP Model



Previous model



-24%
Reduced
space saving

◀ 24 HP Model



Previous model



-20%
Reduced
space saving

◀ 60 HP Combination model

The new compact design not only reduce the installation foot print, but also reduce the time to deliver and install



Previous model




-18%
Reduced
space saving

Sense of endurance

Wider ambient operation

Outdoor temperature range

The combination of new compressor design and system controls have enabled SMMS-7 to expand its allowable operational temperature range




Note : Based on equivalent piping length of 7.5 m and piping height difference of 0 m.

Sense of care

Environmentally - oriented

Reduce refrigerant amount

More than 20% by dedicated cooling design*



*Assumed condition


- Main pipe length : 100 m
- Connected IDU capacity : Same as ODU capacity
- Each IDU capacity : 2HP

>>> Sense of strength

High reliability


◀ DLC (Diamond like carbon) coated vane

Diamond Like Carbon (DLC) protection coating inside "All compressor's vane" increases efficiency and reliability



◀ 2-stage vane

2 stage vane reduce friction and results in a significant improvement in reliability and performance.




»»» Sense of strength

High reliability

◀ Small animal protection

To prevent the small animals from entering and interfering with the electronic components in the system, our new inverter box has been upgraded with additional protection, while allowing reliable operation. The inverter box is fitted with punched sheet metal & resin sheet.



In order to stop small animals get into inverter box, SMMS-7 has resin sheet. It's preventive measure to keep them from shorting out PC boards.




>>> Sense of flexibility

Design flexibility

◀ 200 % Maximum diversity

Thanks to the newly developed refrigerant circuit, the diversity of outdoor units has drastically increased. This makes it much easier to design for installations with many rooms or offices.



Standard model

8HP	10HP	12HP	14HP	16HP	18HP	20HP	22HP	24HP
200%	200%	200%	200%	200%	200%	200%	200%	200%

26HP	28HP	30HP	32HP	34HP	36HP	38HP	40HP
180%	180%	180%	180%	180%	180%	180%	180%

42HP	44HP	46HP	48HP	50HP	52HP	54HP	56HP	58HP	60HP
150%	150%	150%	150%	150%	150%	150%	150%	150%	150%


*Single module

»»» Sense of flexibility

Design flexibility


◀ Total piping length

Applied with Toshiba's unique and greatly improved technology, SMMS-7 can reach up to 1,000 meters maximum piping length.



◀ Farthest pipe from 1st branch

Even more convenient with the piping distance from the first branch to the furthest indoor unit at 90 meters, increasing the flexibility of the installation within the hotel or office building.



◀ Farthest equivalent length

The maximum equivalent distance between outdoor unit and farthest indoor unit tops at 235 meters, which tops the industry class.



◀ Height between indoor units

Another industry's top class is a maximum vertical distance between indoor units which reaches up to 40 meters, equal to an entire 11-storied building. SMMS-7's enhanced piping capabilities result in more benefits for the system design, installation flexibility, as well as the less installation cost.




>>> Sense of convenience

Easy installation and maintenance


◀ Installation flexibility

New system of oil management, balance pipe no longer required.





◀ Easy maintenance

Secure space for maintenance in machine area. Temperature control of liquid pipe leads to removal of liquid tank, leading to reduce refrigerant.



◀ SMMS wave tool

With SMMS wave Tool, you can read and write data from outdoor unit directly on your smart phone without the needs of connecting PC or opening cabinet.




By the new smart phone application, the testing and commissioning can be done without opening the cabinet.




*Smartphone specification : Android™ OS 5.0

◀ The external static pressure

The SMMS-7 units are suitable for challenging installations where high external static pressure performance



Air flow simulation diagram




Note : This result is analytical simulation, that does not guarantee actual temperatures.

◀ New path of heat exchanger

Newly developed to reach max efficiency in cooling operation.

Re-design for cooling realized dedication design of heat exchanger.

*Not suitable for heating by H/E freezing risk due to evaporation temp drops pressure drop loss.




◀ New slim heat exchanger with 24 HP

With 3 pipes rows the heat exchanger has more surface area. This increase contribute to improve the overall performance and at the same time operate more efficiently.




◀ New heat exchanger

Newly developed to reach max efficiency in cooling operation.



◀ 4-way heat exchanger


Heat exchangers are located on all four sides of the outdoor unit, ensuring air flow is equal in all directions.



◀ New developed accumulator


Newly developed accumulator due to decrease pressure drop loss and add parts to improve reliability.

* by delete of J-pipe, additional pipe & valve for return oil need to be added.



◀ New twin rotary compressor

Optimize the system as cooling only model and design new compressor for efficiency improving item.




*Need to be considered as a system for it connect directly oil level management

◀ Blade shapes for a better air flow management




Every single blade is designed with a unique profile, a solution that guarantees a smoother air flow without turbulences.

The new propeller deliver the same amount of air with less sound pressure level.



Outdoor units

Standard model

										
Capacity		8HP	10HP	12HP	14HP	16HP	18HP	20HP	22HP	24HP
Model Name (MMY-)	50 Hz	MAP0807T8P	MAP1007T8P	MAP1207T8P	MAP1407T8P	MAP1607T8P	MAP1807T8P	MAP2007T8P	MAP2207T8P	MAP2407T8P
	60 Hz	MAP0807T7P	MAP1007T7P	MAP1207T7P	MAP1407T7P	MAP1607T7P	MAP1807T7P	MAP2007T7P	MAP2207T7P	MAP2407T7P
Cooling capacity (kW)		22.4	28.0	33.5	40.0	45.0	50.4	56.0	61.5	67.0

															
Capacity		26HP		28HP		30HP		32HP		34HP		36HP		38HP	
Model Name (MMY-)	50 Hz	AP2617T8P		AP2817T8P		AP3017T8P		AP3217T8P		AP3417T8P		AP3617T8P		AP3817T8P	
	60 Hz	AP2617T7P		AP2817T7P		AP3017T7P		AP3217T7P		AP3417T7P		AP3617T7P		AP3817T7P	
Units in combination (MMY-)	MAP1407T8P	MAP1207T8P	MAP1407T8P	MAP1407T8P	MAP1607T8P	MAP1407T8P	MAP1607T8P	MAP1607T8P	MAP1807T8P	MAP1607T8P	MAP1807T8P	MAP1807T8P	MAP2007T8P	MAP1807T8P	
	MAP1407T7P	MAP1207T7P	MAP1407T7P	MAP1407T7P	MAP1607T7P	MAP1407T7P	MAP1607T7P	MAP1607T7P	MAP1807T7P	MAP1607T7P	MAP1807T7P	MAP1807T7P	MAP2007T7P	MAP1807T7P	
Cooling capacity (kW)		73.5		80.0		85.0		90.0		95.4		100.8		106.4	

																	
Capacity		40HP			42HP				44HP			46HP			48HP		
Model Name (MMY-)	50 Hz	AP4017T8P			AP4217T8P				AP4417T8P			AP4617T8P			AP4817T8P		
	60 Hz	AP4017T7P			AP4217T7P				AP4417T7P			AP4617T7P			AP4817T7P		
Units in combination (MMY-)	MAP2007T8P	MAP2007T8P	MAP1407T8P	MAP1407T8P	MAP1407T8P	MAP1607T8P	MAP1407T8P	MAP1407T8P	MAP1807T8P	MAP1407T8P	MAP1407T8P	MAP2007T8P	MAP1407T8P	MAP1407T8P			
	MAP2007T7P	MAP2007T7P	MAP1407T7P	MAP1407T7P	MAP1407T7P	MAP1607T7P	MAP1407T7P	MAP1407T7P	MAP1807T7P	MAP1407T7P	MAP1407T7P	MAP2007T7P	MAP1407T7P	MAP1407T7P			
Cooling capacity (kW)		112.0			120.0				125.0			130.4			136.0		

																			
Capacity		50HP			52HP			54HP			56HP			58HP			60HP		
Model Name (MMY-)	50 Hz	AP5017T8P			AP5217T8P			AP5417T8P			AP5617T8P			AP5817T8P			AP6017T8P		
	60 Hz	AP5017T7P			AP5217T7P			AP5417T7P			AP5617T7P			AP5817T7P			AP6017T7P		
Units in combination (MMY-)	MAP2007T8P	MAP1607T8P	MAP1407T8P	MAP2007T8P	MAP1807T8P	MAP1407T8P	MAP2007T8P	MAP2007T8P	MAP1407T8P	MAP2007T8P	MAP2007T8P	MAP1607T8P	MAP2007T8P	MAP2007T8P	MAP1807T8P	MAP2007T8P	MAP2007T8P	MAP2007T8P	
	MAP2007T7P	MAP1607T7P	MAP1407T7P	MAP2007T7P	MAP1807T7P	MAP1407T7P	MAP2007T7P	MAP2007T7P	MAP1407T7P	MAP2007T7P	MAP2007T7P	MAP1607T7P	MAP2007T7P	MAP2007T7P	MAP1807T7P	MAP2007T7P	MAP2007T7P	MAP2007T7P	
Cooling capacity (kW)		141.0			146.4			152.0			157.0			162.4			168.0		

* Power: 3-phase 50 Hz 400V (380 - 415V) / 3-phase 60 Hz 380V
 * The source voltage must not fluctuate more than ±10%.
 * Rated conditions
 Cooling: Indoor air temperature 27°C DB/19°C WB, outdoor air temperature 35°C DB

High efficiency Model

Capacity		14HP		16HP		18HP		20HP		22HP		24HP	
Model Name (MMY-)	50 Hz	MAP14A7T8P		AP1627T8P		AP1827T8P		AP2027T8P		AP2227T8P		AP2427T8P	
	60 Hz	MAP14A7T7P		AP1627T7P		AP1827T7P		AP2027T7P		AP2227T7P		AP2427T7P	
Units in combination (MMY-)		-		MAP0807T8P MAP0807T7P	MAP0807T8P MAP0807T7P	MAP1007T8P MAP1007T7P	MAP0807T8P MAP0807T7P	MAP1007T8P MAP1007T7P	MAP1007T8P MAP1007T7P	MAP1207T8P MAP1207T7P	MAP1007T8P MAP1007T7P	MAP0807T8P MAP0807T7P	MAP0807T8P MAP0807T7P
Cooling capacity (kW)		40.0		44.8		50.4		56.0		61.5		67.2	

Capacity		26HP		28HP		30HP			32HP			34HP		
Model Name (MMY-)	50 Hz	AP2627T8P		AP2827T8P		AP3027T8P			AP3227T8P			AP3427T8P		
	60 Hz	AP2627T7P		AP2827T7P		AP3027T7P			AP3227T7P			AP3427T7P		
Units in combination (MMY-)		MAP14A7T8P MAP14A7T7P	MAP1207T8P MAP1207T7P	MAP14A7T8P MAP14A7T7P	MAP14A7T8P MAP14A7T7P	MAP1007T8P MAP1007T7P	MAP1007T8P MAP1007T7P	MAP1007T8P MAP1007T7P	MAP1207T8P MAP1207T7P	MAP1007T8P MAP1007T7P	MAP1007T8P MAP1007T7P	MAP1207T8P MAP1207T7P	MAP1207T8P MAP1207T7P	MAP1007T8P MAP1007T7P
Cooling capacity (kW)		73.5		80.0		84.0			89.5			95.0		

Capacity		36HP			38HP			40HP			42HP		
Model Name (MMY-)	50 Hz	AP3627T8P			AP3827T8P			AP4027T8P			AP4227T8P		
	60 Hz	AP3627T7P			AP3827T7P			AP4027T7P			AP4227T7P		
Units in combination (MMY-)		MAP1207T8P MAP1207T7P	MAP1207T8P MAP1207T7P	MAP1207T8P MAP1207T7P	MAP14A7T8P MAP14A7T7P	MAP1207T8P MAP1207T7P	MAP1207T8P MAP1207T7P	MAP14A7T8P MAP14A7T7P	MAP14A7T8P MAP14A7T7P	MAP1207T8P MAP1207T7P	MAP14A7T8P MAP14A7T7P	MAP14A7T8P MAP14A7T7P	MAP14A7T8P MAP14A7T7P
Cooling capacity (kW)		105.0			107.0			113.5			120.0		

Capacity		44HP			46HP			48HP			50HP			52HP			54HP		
Model Name (MMY-)	50 Hz	AP4427T8P			AP4627T8P			AP4827T8P			AP5027T8P			AP5227T8P			AP5427T8P		
	60 Hz	AP4427T7P			AP4627T7P			AP4827T7P			AP5027T7P			AP5227T7P			AP5427T7P		
Units in combination (MMY-)		MAP1607T8P MAP1607T7P	MAP14A7T8P MAP14A7T7P	MAP14A7T8P MAP14A7T7P	MAP1807T8P MAP1807T7P	MAP14A7T8P MAP14A7T7P	MAP14A7T8P MAP14A7T7P	MAP1607T8P MAP1607T7P	MAP1607T8P MAP1607T7P	MAP1607T8P MAP1607T7P	MAP1807T8P MAP1807T7P	MAP1607T8P MAP1607T7P	MAP1607T8P MAP1607T7P	MAP1807T8P MAP1807T7P	MAP1807T8P MAP1807T7P	MAP1607T8P MAP1607T7P	MAP1607T8P MAP1607T7P	MAP1807T8P MAP1807T7P	
Cooling capacity (kW)		125.0			130.4			135.0			140.4			145.8			151.2		

	Y-shape branching joint				Branch headers				Outdoor unit connection piping kit					
Appearance														
Model name	RBM-BY55E	RBM-BY105E	RBM-BY205E	RBM-BY305E	RBM-HY1043E	RBM-HY2043E	RBM-HY1083E	RBM-HY2083E	RBM-BT14E		RBM-BT24E			
Usage (Classification according to indoor unit capacity code)	Total below 6.4				Total 6.4 or more and below 14.2		Total 14.2 or more and below 25.2		Total 25.2 or more		Max.4 branches Total below 14.2		Max.8 branches Total 14.2 or more and below 25.2	
	Total below 26.0		Total 26.0 or more											

* Anti-Corrosion protection model : MMY-MAP****T8JP, MMY-MAP****T7JP

Outdoor unit specifications

Standard model (Single unit)

Equivalent HP			8HP	10HP	12HP	14HP	16HP
Model name	50Hz (MMY-)		MAP0807T8P	MAP1007T8P	MAP1207T8PS-ID	MAP1407T8P	MAP1607T8P
	60Hz (MMY-)		MAP0807T7P	MAP1007T7P	MAP1207T7P	MAP1407T7P	MAP1607T7P
Outdoor unit type			Inverter				
Power supply (*1)			3phase 4wires 50Hz 400V (380-415V)/3phase 4 wires 60Hz 380 Hz				
Cooling (*2)	Capacity 100%		(kW/Btu/h) 22.4 / 76,400	28.0 / 95,500	33.5 / 114,000	40.0 / 136,000	45.0 / 154,000
	Power consumption		(kW) 4.65	6.57	8.12	11.4	12.5
	EER (Energy Efficiency Ratio)	Capacity 100%	4.82	4.26	4.13	3.50	3.60
		Capacity 80%	5.79	5.31	5.25	4.32	4.32
		Capacity 50%	7.27	7.11	6.58	5.78	5.75
External dimensions (Height / Width / Depth)			(mm) 1,800 / 990 / 780	1,800 / 990 / 780	1,800 / 990 / 780	1,800 / 990 / 780	1,800 / 1,210 / 780
Total weight			(kg) 200	200	200	200	281
Compressor	Motor output		(kW) 4.0 x 1	5.8 x 1	7.1 x 1	10.0 x 1	5.5 x 2
	Motor output		(kW) 1.0	1.0	1.0	1.0	1.0
Fan unit	Air volume		(m ³ /h) 9,700	9,700	12,200	12,200	12,600
	Refrigerant piping	Gas side	(mm) ø 19.1	ø 22.2	ø 28.6	ø 28.6	ø 28.6
Main pipe diameter		Liquid side	(mm) ø 12.7	ø 12.7	ø 12.7	ø 15.9	ø 15.9
Sound pressure level			(dB(A)) 55	57	60	61	61
Diversity ^(*)			200%	200%	200%	200%	200%
Max. external static pressure			(Pa) 60	60	50	40	40

Standard model (Single unit)

Equivalent HP			18HP	20HP	22HP	24HP
Model name	50Hz (MMY-)		MAP1807T8P	MAP2007T8P	MAP2207T8P	MAP2407T8P
	60Hz (MMY-)		MAP1807T7P	MAP2007T7P	MAP2207T7P	MAP2407T7P
Outdoor unit type			Inverter			
Power supply (*1)			3phase 4wires 50Hz 400V (380-415V) / 3phase 4wires 60Hz 380V			
Cooling (*2)	Capacity 100%		(kW/Btu/h) 50.4 / 172,000	56.0 / 191,000	61.5 / 213,000	67.0 / 230,000
	Power consumption		(kW) 14.8	17.4	18.6	22.9
	EER (Energy Efficiency Ratio)	Capacity 100%	3.40	3.22	3.30	2.93
		Capacity 80%	4.15	3.93	4.00	3.67
		Capacity 50%	5.82	5.61	5.39	4.75
External dimensions (Height / Width / Depth)			(mm) 1,800/1,210/780	1,800/1,210/780	1,800/1,600/780	1,800/1,600/780
Total weight			(kg) 281	281	340	340
Compressor	Motor output		(kW) 6.6 x 2	7.8 x 2	8.2 x 2	10.3 x 2
	Motor output		(kW) 1.0	1.0	2.0	2.0
Fan unit	Air volume		(m ³ /h) 12,600	12,600	18,500	18,500
	Refrigerant piping	Gas side	(mm) ø 28.6	ø 28.6	ø 28.6	ø 34.9
Main pipe diameter		Liquid side	(mm) ø 15.9	ø 15.9	ø 19.1	ø 19.1
Sound pressure level			(dB(A)) 61	61	63	63
Diversity ^(*)			200%	200%	200%	200%
Max. external static pressure			(Pa) 40	40	40	40

Outdoor unit specifications

Standard model (Combination)

Equivalent HP		26HP		28HP		30HP		
Model name	50Hz (MMY-)	AP2617T8P		AP2817T8P		AP3017T8P		
	60Hz (MMY-)	AP2617T7P		AP2817T7P		AP3017T7P		
Outdoor unit type	Inverter							
Power supply (*1)	3phase 4wires 50Hz 400V (380-415V) / 3phase 4wires 60Hz 380V							
Outdoor unit model	50Hz (MMY-)	MAP1407T8P	MAP1207T8P	MAP1407T8P	MAP1407T8P	MAP1607T8P	MAP1407T8P	
	60Hz (MMY-)	MAP1407T7P	MAP1207T7P	MAP1407T7P	MAP1407T7P	MAP1607T7P	MAP1407T7P	
Cooling (*2)	Capacity 100%	73.5 / 247,000		80.0 / 268,000		85.0 / 285,000		
	Power consumption	19.7		22.9		23.9		
	EER (Energy Efficiency Ratio)	Capacity 100%	3.73		3.50		3.55	
		Capacity 80%	4.63		4.32		4.33	
		Capacity 50%	6.00		5.77		5.77	
Total weight	(kg)	200	200	200	200	281	200	
Compressor	Motor output	10.0 x 1		10.0 x 1		5.5 x 2		
	Motor output	1.0		1.0		1.0		
Fan unit	Motor output	1.0		1.0		1.0		
	Air volume	12,200		12,200		12,600		
Refrigerant piping	Main pipe diameter	Gas side (mm)	ø 34.9		ø 34.9		ø 34.9	
		Liquid side (mm)	ø 19.1		ø 19.1		ø 19.1	
Sound pressure level	(dB(A))	63.5		64.0		64.0		
Diversity ^(*)		180%		180%		180%		

Standard model (Combination)

Equivalent HP		32HP		34HP		36HP		
Model name	50Hz (MMY-)	AP3217T8P		AP3417T8P		AP3617T8P		
	60Hz (MMY-)	AP3217T7P		AP3417T7P		AP3617T7P		
Outdoor unit type	Inverter							
Power supply (*1)	3phase 4wires 50Hz 400V (380-415V) / 3phase 4wires 60Hz 380V							
Outdoor unit model	50Hz (MMY-)	MAP1607T8P	MAP1607T8P	MAP1807T8P	MAP1607T8P	MAP1807T8P	MAP1807T8P	
	60Hz (MMY-)	MAP1607T7P	MAP1607T7P	MAP1807T7P	MAP1607T7P	MAP1807T7P	MAP1807T7P	
Cooling (*2)	Capacity 100%	90.0 / 305,000		95.4 / 324,000		100.8 / 341,000		
	Power consumption	25.0		27.3		29.6		
	EER (Energy Efficiency Ratio)	Capacity 100%	3.60		3.49		3.40	
		Capacity 80%	4.31		4.24		4.15	
		Capacity 50%	5.76		5.79		5.79	
Total weight	(kg)	281	281	281	281	281	281	
Compressor	Motor output	5.5 x 2		6.6 x 2		6.6 x 2		
	Motor output	1.0		1.0		1.0		
Fan unit	Motor output	1.0		1.0		1.0		
	Air volume	12,600		12,600		12,600		
Refrigerant piping	Main pipe diameter	Gas side (mm)	ø 34.9		ø 34.9		ø 41.3	
		Liquid side (mm)	ø 19.1		ø 19.1		ø 22.2	
Sound pressure level	(dB(A))	64.0		64.0		64.0		
Diversity ^(*)		180%		180%		180%		

*1 The source voltage must not fluctuate more than ±10%.

*2 Rated conditions Cooling : Indoor air temperature 27°C DB/19°C WB, Outdoor air temperature 35°C DB

Based on equivalent piping length of 7.5 m and piping height difference of 0 m.

*3 Be sure to refer to the Engineering Data book for details of those conditions and requirements.

Outdoor unit specifications

Standard model (Combination)

Equivalent HP		38HP			40HP		42HP			
Model name	50Hz (MMY-)	AP3817T8P			AP4017T8P		AP4217T8P			
	60Hz (MMY-)	AP3817T7P			AP4017T7P		AP4217T7P			
Outdoor unit type	Inverter									
Power supply (*)	3phase 4wires 50Hz 400V (380-415V) / 3phase 4wires 60Hz 380V									
Outdoor unit model	50Hz (MMY-)	MAP2007T8P	MAP1807T8P	MAP2007T8P	MAP2007T8P	MAP1407T8P	MAP1407T8P	MAP1407T8P	MAP1407T8P	
	60Hz (MMY-)	MAP2007T7P	MAP1807T7P	MAP2007T7P	MAP2007T7P	MAP1407T7P	MAP1407T7P	MAP1407T7P	MAP1407T7P	
Cooling (**)	Capacity 100%	106.4 / 362,000			112.0 / 382,000		120.0 / 399,000			
	Power consumption	(kW) 32.1			34.8		34.3			
	EER (Energy Efficiency Ratio)	Capacity 100%	3.31			3.22		3.50		
		Capacity 80%	4.03			3.91		4.32		
Capacity 50%		5.71			5.61		5.77			
Total weight	281		281	281	281	200	200	200		
Compressor	Motor output	(kW) 7.8 x 2		6.6 x 2	7.8 x 2	7.8 x 2	10.0 x 1	10.0 x 1	10.0 x 1	
	Fan unit	Motor output (kW) 1.0		1.0	1.0	1.0	1.0	1.0	1.0	
Air volume	(m ³ /h) 12,600		12,600	12,600	12,600	12,600	12,200	12,200	12,200	
	Refrigerant piping	Main pipe diameter	Gas side (mm)	ø 41.3		ø 41.3		ø 41.3		
Liquid side (mm)		ø 22.2		ø 22.2		ø 22.2				
Sound pressure level	(dB(A) 64.0		64.0		64.0		66.0			
Diversity ^(*)	180%		180%		180%		150%			

Technical specifications

Standard model (Combination)

Equivalent HP		44HP			46HP			48HP			
Model name	50Hz (MMY-)	AP4417T8P			AP4617T8P			AP4817T8P			
	60Hz (MMY-)	AP4417T7P			AP4617T7P			AP4817T7P			
Outdoor unit type	Inverter										
Power supply (*)	3phase 4wires 50Hz 400V (380-415V) / 3phase 4wires 60Hz 380V										
Outdoor unit model	50Hz (MMY-)	MAP1607T8P	MAP1407T8P	MAP1407T8P	MAP1807T8P	MAP1407T8P	MAP1407T8P	MAP2007T8P	MAP1407T8P	MAP1407T8P	
	60Hz (MMY-)	MAP1607T7P	MAP1407T7P	MAP1407T7P	MAP1807T7P	MAP1407T7P	MAP1407T7P	MAP2007T7P	MAP1407T7P	MAP1407T7P	
Cooling (**)	Capacity 100%	125.0 / 416,000			130.4 / 437,000			136.0 / 457,000			
	Power consumption	(kW) 35.3			37.7			40.2			
	EER (Energy Efficiency Ratio)	Capacity 100%	3.54			3.46			3.38		
		Capacity 80%	4.33			4.26			4.15		
Capacity 50%		5.79			5.77			5.71			
Total weight	281		200	200	281	200	200	281	200	200	
Compressor	Motor output	(kW) 5.5 x 2		10.0 x 1	10.0 x 1	6.6 x 2	10.0 x 1	10.0 x 1	7.8 x 2	10.0 x 1	10.0 x 1
	Fan unit	Motor output (kW) 1.0		1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Air volume	(m ³ /h) 12,600		12,200	12,200	12,600	12,200	12,200	12,600	12,200	12,200	
	Refrigerant piping	Main pipe diameter	Gas side (mm)	ø 41.3		ø 41.3		ø 41.3			
Liquid side (mm)		ø 22.2		ø 22.2		ø 22.2					
Sound pressure level	(dB(A) 66.0		66.0		66.0		66.0				
Diversity ^(*)	150%		150%		150%		150%				

Technical specifications

Standard model (Combination)

											Technical specifications		
Equivalent HP			50HP			52HP			54HP				
Model name	50Hz (MMY-)		AP5017T8P			AP5217T8P			AP5417T8P				
	60Hz (MMY-)		AP5017T7P			AP5217T7P			AP5417T7P				
Outdoor unit type											Inverter		
Power supply (*2)											3phase 4wires 50Hz 400V (380-415V) / 3phase 4wires 60Hz 380V		
Outdoor unit model	50Hz (MMY-)	MAP2007T8P	MAP1607T8P	MAP1407T8P	MAP2007T8P	MAP1807T8P	MAP1407T8P	MAP2007T8P	MAP2007T8P	MAP1407T8P			
	60Hz (MMY-)	MAP2007T7P	MAP1607T7P	MAP1407T7P	MAP2007T7P	MAP1807T7P	MAP1407T7P	MAP2007T7P	MAP2007T7P	MAP1407T7P			
Cooling (*1)	Capacity 100%	(kW/Btu/h)	141.0 / 478,000			146.4 / 498,000			152.0 / 512,000				
	Power consumption	(kW)	41.2			43.6			46.2				
	EER (Energy Efficiency Ratio)	Capacity 100%		3.42			3.36			3.29			
		Capacity 80%		4.15			4.09			4.01			
Capacity 50%			5.69			5.72			5.67				
Total weight		(kg)	281	281	200	281	281	200	281	281	200		
Compressor	Motor output	(kW)	7.8 x 2	5.5 x 2	10.0 x 1	7.8 x 2	6.6 x 2	10.0 x 1	7.8 x 2	7.8 x 2	10.0 x 1		
	Motor output	(kW)	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0		
Fan unit	Air volume	(m ³ /h)	12,600	12,600	12,200	12,600	12,600	12,200	12,600	12,600	12,200		
	Refrigerant piping	Main pipe diameter	Gas side (mm)	ø 41.3			ø 41.3			ø 41.3			
Liquid side (mm)		ø 22.2			ø 22.2			ø 22.2					
Sound pressure level		(dB(A))	66.0			66.0			66.0				
Diversity(*3)			150%			150%			150%				

Standard model (Combination)

											Technical specifications		
Equivalent HP			56HP			58HP			60HP				
Model name	50Hz (MMY-)		AP5617T8P			AP5817T8P			AP6017T8P				
	60Hz (MMY-)		AP5617T7P			AP5817T7P			AP6017T7P				
Outdoor unit type											Inverter		
Power supply (*2)											3phase 4wires 50Hz 400V (380-415V) / 3phase 4wires 60Hz 380V		
Outdoor unit model	50Hz (MMY-)	MAP2007T8P	MAP2007T8P	MAP1607T8P	MAP2007T8P	MAP2007T8P	MAP1807T8P	MAP2007T8P	MAP2007T8P	MAP2007T8P			
	60Hz (MMY-)	MAP2007T7P	MAP2007T7P	MAP1607T7P	MAP2007T7P	MAP2007T7P	MAP1807T7P	MAP2007T7P	MAP2007T7P	MAP2007T7P			
Cooling (*1)	Capacity 100%	(kW/Btu/h)	157.0 / 532,000			162.4 / 553,000			168.0 / 573,000				
	Power consumption	(kW)	47.1			49.5			52.2				
	EER (Energy Efficiency Ratio)	Capacity 100%		3.33			3.28			3.22			
		Capacity 80%		4.03			3.98			3.92			
Capacity 50%			5.65			5.68			5.60				
Total weight		(kg)	281	281	281	281	281	281	281	281			
Compressor	Motor output	(kW)	7.8 x 2	7.8 x 2	5.5 x 2	7.8 x 2	7.8 x 2	6.6 x 2	7.8 x 2	7.8 x 2	7.8 x 2		
	Motor output	(kW)	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0		
Fan unit	Air volume	(m ³ /h)	12,600	12,600	12,600	12,600	12,600	12,600	12,600	12,600	12,600		
	Refrigerant piping	Main pipe diameter	Gas side (mm)	ø 41.3			ø 41.3			ø 41.3			
Liquid side (mm)		ø 22.2			ø 22.2			ø 22.2					
Sound pressure level		(dB(A))	66.0			66.0			66.0				
Diversity(*3)			150%			150%			150%				

*1 The source voltage must not fluctuate more than ±10%.

*2 Rated conditions Cooling : Indoor air temperature 27°C DB/19°C WB, Outdoor air temperature 35°C DB
Based on equivalent piping length of 7.5 m and piping height difference of 0 m.

*3 Be sure to refer to the Engineering Data book for details of those conditions and requirements.

Outdoor unit specifications

High efficiency model (Single unit/Combination)

Equivalent HP			14HP	16HP	18HP		
Model name	50Hz (MMY-)	MAP14A7T8P	MAP14A7T8P	AP1627T8P	AP1827T8P		
	60Hz (MMY-)	MAP14A7T7P	MAP14A7T7P	AP1627T7P	AP1827T7P		
Outdoor unit type	Inverter						
Power supply (*1)	3phase 4wires 50Hz 400V (380-415V) / 3phase 4wires 60Hz 380V						
Outdoor unit model	50Hz (MMY-)	MAP14A7T8P	MAP0807T8P	MAP0807T8P	MAP1007T8P	MAP0807T8P	
	60Hz (MMY-)	MAP14A7T7P	MAP0807T7P	MAP0807T7P	MAP1007T7P	MAP0807T7P	
Cooling (*2)	Capacity 100%	(kW/Btu/h)	40.0 / 136,000	40.0 / 154,000	50.4 / 172,000		
	Power consumption	(kW)	10.4	9.29	11.2		
	EER (Energy Efficiency Ratio)	Capacity 100%		3.85	4.82	4.51	
		Capacity 80%		4.58	5.79	5.51	
Capacity 50%			5.92	7.27	7.18		
External dimensions (Height / Width / Depth)	(mm)	1,800 / 1,210 / 780	1,800 / 990 / 780	1,800 / 990 / 780	1,800 / 990 / 780	1,800 / 990 / 780	
Total weight	(kg)	281	200	200	200	200	
Compressor	Motor output	(kW)	4.6 x 2	4.0 x 1	4.0 x 1	5.8x1	4.0x1
Fan unit	Motor output	(kW)	1.0	1.0	1.0	1.0	1.0
	Air volume	(m ³ /h)	12,200	9,700	9,700	9,700	9,700
Refrigerant piping	Main pipe diameter	Gas side (mm)	ø 28.6	ø 28.6	ø 28.6	ø 28.6	
		Liquid side (mm)	ø 15.9	ø 15.9	ø 15.9	ø 15.9	
Sound pressure level	(dB(A))	60	58.0	58.0	59.5	59.5	
Diversity ^{(*)3}		200%	180%	180%	180%	180%	
Max.external static pressure	(Pa)	50					

High efficiency model (Combination)

Equivalent HP			20HP	22HP	24HP				
Model name	50Hz (MMY-)	AP2027T8P	AP2027T8P	AP2227T8P	AP2427T8P				
	60Hz (MMY-)	AP2027T7P	AP2027T7P	AP2227T7P	AP2427T7P				
Outdoor unit type	Inverter								
Power supply (*1)	3phase 4wires 50Hz 400V (380-415V) / 3phase 4wires 60Hz 380V								
Outdoor unit model	50Hz (MMY-)	MAP1007T8P	MAP1007T8P	MAP1207T8P	MAP1007T8P	MAP0807T8P	MAP0807T8P		
	60Hz (MMY-)	MAP1007T7P	MAP1007T7P	MAP1207T7P	MAP1007T7P	MAP0807T7P	MAP0807T7P	MAP0807T7P	
Cooling (*2)	Capacity 100%	(kW/Btu/h)	56.0 / 191,000	61.5 / 213,000	67.2 / 230,000				
	Power consumption	(kW)	13.1	14.9	13.9				
	EER (Energy Efficiency Ratio)	Capacity 100%		4.26	4.12	4.82			
		Capacity 80%		5.31	5.16	5.80			
Capacity 50%			7.11	6.64	7.27				
External dimensions (Height / Width / Depth)	(mm)	1,800/990/780	1,800/990/780	1,800/990/780	1,800/990/780	1,800/990/780	1,800/990/780		
Total weight	(kg)	200	200	200	200	200	200		
Compressor	Motor output	(kW)	5.8 x 1	5.8 x 1	7.1x1	5.8 x 1	4.0 x 1	4.0 x 1	4.0 x 1
Fan unit	Motor output	(kW)	1.0	1.0	1.0	1.0	1.0	1.0	1.0
	Air volume	(m ³ /h)	9,700	9,700	12,200	9,700	9,700	9,700	9,700
Refrigerant piping	Main pipe diameter	Gas side (mm)	ø 28.6	ø 28.6	ø 28.6	ø 34.9			
		Liquid side (mm)	ø 15.9	ø 19.1	ø 19.1	ø 19.1			
Sound pressure level	(dB(A))	60.0	62.0	62.0	60.0	60.0			
Diversity ^{(*)3}		180%	180%	180%	150%	150%			

Outdoor unit specifications

High efficiency model (Combination)

Equivalent HP			26HP		28HP		30HP		
Model name	50Hz (MMY-)	AP2627T8PS-ID	AP2827T8PS-ID		AP3027T8P				
	60Hz (MMY-)	AP2627T7P	AP2827T7P		AP3027T7P				
Outdoor unit type	Inverter								
Power supply (*1)	3phase 4wires 50Hz 400V (380-415V) / 3phase 4wires 60Hz 380V								
Outdoor unit model	50Hz (MMY-)	MAP14A7T8P	MAP1207T8P	MAP14A7T8P	MAP14A7T8P	MAP1007T8P	MAP1007T8P	MAP1007T8P	
	60Hz (MMY-)	MAP14A7T7P	MAP1207T7P	MAP14A7T7P	MAP14A7T7P	MAP1007T7P	MAP1007T7P	MAP1007T7P	
Cooling (*2)	Capacity 100%	73.5 / 247,000		80.0 / 268,000		84.0 / 285,000			
	Power consumption	17.9		19.6		19.7			
	EER (Energy Efficiency Ratio)	Capacity 100%	4.10		4.08		4.26		
		Capacity 80%	4.98		4.74		5.29		
Capacity 50%		6.34		6.15		7.09			
External dimensions (Height / Width / Depth)	(mm)	1,800 / 1,210 / 780	1,800 / 990 / 780	1,800 / 1,210 / 780	1,800 / 1,210 / 780	1,800 / 990 / 780	1,800 / 990 / 780	1,800 / 990 / 780	
Total weight	(kg)	281	200	281	281	200	200	200	
Compressor	Motor output	(kW)	4.6 x 2	7.1 x 1	4.6 x 2	4.6 x 2	5.8 x 1	5.8 x 1	
	Motor output	(kW)	1.0	1.0	1.0	1.0	1.0	1.0	
Fan unit	Motor output	(kW)	1.0	1.0	1.0	1.0	1.0	1.0	
	Air volume	(m ³ /h)	12,200	12,200	12,200	12,200	9,700	9,700	
Refrigerant piping	Main pipe diameter	Gas side (mm)	ø 34.9		ø 34.9		ø 34.9		
		Liquid side (mm)	ø 19.1		ø 19.1		ø 19.1		
Sound pressure level	(dB(A))	63.0		63		62.0			
Diversity ^{(*)3}		180%		180%		150%			

High efficiency model (Combination)

Equivalent HP			32HP			34HP			36HP		
Model name	50Hz (MMY-)	AP3227T8P	AP3427T8P			AP3627T8P					
	60Hz (MMY-)	AP3227T7P	AP3427T7P			AP3627T7P					
Outdoor unit type	Inverter										
Power supply (*1)	3phase 4wires 50Hz 400V (380-415V) / 3phase 4wires 60Hz 380V										
Outdoor unit model	50Hz (MMY-)	MAP1207T8P	MAP1007T8P	MAP1007T8P	MAP1207T8P	MAP1207T8P	MAP1007T8P	MAP1207T8P	MAP1207T8P	MAP1207T8P	
	60Hz (MMY-)	MAP1207T7P	MAP1007T7P	MAP1007T7P	MAP1207T7P	MAP1207T7P	MAP1007T7P	MAP1207T7P	MAP1207T7P	MAP1207T7P	
Cooling (*2)	Capacity 100%	89.5 / 305,000			95.0 / 324,000			100.5 / 341,000			
	Power consumption	21.5			23.3			25.1			
	EER (Energy Efficiency Ratio)	Capacity 100%	4.16			4.08			4.00		
		Capacity 80%	5.19			5.10			5.03		
Capacity 50%		6.78			6.50			6.28			
External dimensions (Height / Width / Depth)	(mm)	1,800/990/780	1,800/990/780	1,800/990/780	1,800/990/780	1,800/990/780	1,800/990/780	1,800/990/780	1,800/990/780	1,800/990/780	
Total weight	(kg)	200	200	200	200	200	200	200	200	200	
Compressor	Motor output	(kW)	7.1 x 1	5.8 x 1	5.8 x 1	7.1 x 1	7.1 x 1	5.8 x 1	7.1 x 1	7.1 x 1	
	Motor output	(kW)	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	
Fan unit	Motor output	(kW)	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	
	Air volume	(m ³ /h)	12,200	9,700	9,700	12,200	12,200	9,700	12,200	12,200	
Refrigerant piping	Main pipe diameter	Gas side (mm)	ø 34.9			ø 34.9			ø 41.3		
		Liquid side (mm)	ø 19.1			ø 19.1			ø 22.2		
Sound pressure level	(dB(A))	63.0			64.0			65.0			
Diversity ^{(*)3}		150%			150%			150%			

*1 The source voltage must not fluctuate more than ±10%.

*2 Rated conditions Cooling : Indoor air temperature 27°C DB/19°C WB, Outdoor air temperature 35°C DB

Based on equivalent piping length of 7.5 m and piping height difference of 0 m.

*3 Be sure to refer to the Engineering Data book for details of those conditions and requirements.

Outdoor unit specifications

High efficiency model (Combination)

Equivalent HP		38HP			40HP			42HP			
Model name	50Hz (MMY-)	AP3827T8P			AP4027T8PS-ID			AP4227T8PS-ID			
	60Hz (MMY-)	AP3827T7P			AP4027T7P			AP4217T7P			
Outdoor unit type		Inverter									
Power supply (*1)		3phase 4wires 50Hz 400V (380-415V) / 3phase 4wires 60Hz 380V									
Outdoor unit model	50Hz (MMY-)	MAP14A7T8P	MAP1207T8P	MAP1207T8P	MAP14A7T8P	MAP14A7T8P	MAP1207T8P	MAP14A7T8P	MAP14A7T8P	MAP14A7T8P	
	60Hz (MMY-)	MAP14A7T7P	MAP1207T7P	MAP1207T7P	MAP14A7T7P	MAP14A7T7P	MAP1207T7P	MAP14A7T7P	MAP14A7T7P	MAP14A7T7P	
Cooling (*2)	Capacity 100%	107.0 / 362,000			113.5 / 382,000			120.0 / 399,000			
	Power consumption	27.2			27.7			29.4			
	EER (Energy Efficiency Ratio)	Capacity 100%	3.94			4.09			4.08		
		Capacity 80%	4.86			4.88			4.80		
Capacity 50%		6.14			6.31			6.17			
External dimensions (Height / Width / Depth)		(mm)	1,800/1,210/780	1,800/990/780	1,800/990/780	1,800/1,210/780	1,800/1,210/780	1,800/990/780	1,800/1,210/780	1,800/1,210/780	
Total weight		(kg)	281	200	200	281	281	200	281	281	
Compressor	Motor output	(kW)	4.6 x 2	7.1 x 1	7.1 x 1	4.6 x 2	4.6 x 2	7.1 x 2	4.6 x 2	4.6 x 2	
	Motor output	(kW)	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	
Fan unit	Motor output	(kW)	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	
	Air volume	(m ³ /h)	12,200	12,200	12,200	12,200	12,200	12,200	12,200	12,200	
Refrigerant piping	Main pipe diameter	Gas side	ø 41.3			ø 41.3			ø 41.3		
		Liquid side	ø 22.2			ø 22.2			ø 22.2		
Sound pressure level		(dB(A))	65.0			65.0			65.0		
Diversity(*3)			150%			150%			150%		

High efficiency model (Combination)

Equivalent HP		44HP			46HP			48HP			
Model name	50Hz (MMY-)	AP4427T8P			AP4627T8P			AP4827T8P			
	60Hz (MMY-)	AP4427T7P			AP4627T7P			AP4827T7P			
Outdoor unit type		Inverter									
Power supply (*1)		3phase 4wires 50Hz 400V (380-415V) / 3phase 4wires 60Hz 380V									
Outdoor unit model	50Hz (MMY-)	MAP1607T8P	MAP14A7T8P	MAP14A7T8P	MAP1807T8P	MAP14A7T8P	MAP14A7T8P	MAP1607T8P	MAP1607T8P	MAP1607T8P	
	60Hz (MMY-)	MAP1607T7P	MAP14A7T7P	MAP14A7T7P	MAP1807T7P	MAP14A7T7P	MAP14A7T7P	MAP1607T7P	MAP1607T7P	MAP1607T7P	
Cooling (*2)	Capacity 100%	125.0 / 416,000			130.4 / 437,000			135.0 / 457,000			
	Power consumption	33.2			35.5			37.5			
	EER (Energy Efficiency Ratio)	Capacity 100%	3.76			3.67			3.60		
		Capacity 80%	4.48			4.40			4.32		
Capacity 50%		5.84			5.87			5.77			
External dimensions (Height / Width / Depth)		(mm)	1,800/1,210/780	1,800/1,210/780	1,800/1,210/780	1,800/1,210/780	1,800/1,210/780	1,800/1,210/780	1,800/1,210/780	1,800/1,210/780	
Total weight		(kg)	281	281	281	281	281	281	281	281	
Compressor	Motor output	(kW)	5.5 x 2	4.6 x 2	4.6 x 2	6.6 x 2	4.6 x 2	4.6 x 2	5.5 x 2	5.5 x 2	
	Motor output	(kW)	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	
Fan unit	Motor output	(kW)	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	
	Air volume	(m ³ /h)	12,600	12,200	12,200	12,600	12,200	12,200	12,600	12,600	
Refrigerant piping	Main pipe diameter	Gas side	ø 41.3			ø 41.3			ø 41.3		
		Liquid side	ø 22.2			ø 22.2			ø 22.2		
Sound pressure level		(dB(A))	65.5			65.5			66.0		
Diversity(*3)			150%			150%			150%		

Outdoor unit specifications

High efficiency model (Combination)

											Technical specifications	
Equivalent HP		50HP			52HP			54HP				
Model name	50Hz (MMY-)	AP5027T8P			AP5227T8P			AP5427T8P				
	60Hz (MMY-)	AP5027T7P			AP5227T7P			AP5427T7P				
Outdoor unit type		Inverter										
Power supply (*1)		3phase 4wires 50Hz 400V (380-415V) / 3phase 4wires 60Hz 380V										
Outdoor unit model	50Hz (MMY-)	MAP1807T8P	MAP1607T8P	MAP1607T8P	MAP1807T8P	MAP1807T8P	MAP1607T8P	MAP1807T8P	MAP1807T8P	MAP1807T8P		
	60Hz (MMY-)	MAP1807T7P	MAP1607T7P	MAP1607T7P	MAP1807T7P	MAP1807T7P	MAP1607T7P	MAP1807T7P	MAP1807T7P	MAP1807T7P		
Cooling (*2)	Capacity 100%	140.4 / 478,000			145.8 / 498,000			151.2 / 512,000				
	Power consumption	39.8			42.1			44.5				
	EER (Energy Efficiency Ratio)	Capacity 100%	3.53			3.46			3.40			
		Capacity 80%	4.25			4.19			4.16			
Capacity 50%		5.80			5.79			5.82				
External dimensions (Height / Width / Depth)		(mm)	1,800/1,210/780	1,800/1,210/780	1,800/1,210/780	1,800/1,210/780	1,800/1,210/780	1,800/1,210/780	1,800/1,210/780	1,800/1,210/780		
Total weight		(kg)	281	281	281	281	281	281	281	281		
Compressor	Motor output	(kW)	6.6 x 2	5.5 x 2	5.5 x 2	6.6 x 2	6.6 x 2	5.5 x 2	6.6 x 2	6.6 x 2		
	Motor output	(kW)	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0		
Fan unit	Air volume	(m ³ /h)	12,600	12,600	12,600	12,600	12,600	12,600	12,600	12,600		
	Refrigerant piping	Main pipe diameter	Gas side (mm)	ø 41.3			ø 41.3			ø 41.3		
		Liquid side (mm)	ø 22.2			ø 22.2			ø 22.2			
Sound pressure level		(dB(A))	66.0			66.0			66.0			
Diversity ^(*3)			150%			150%			150%			

*1 The source voltage must not fluctuate more than ±10%.

*2 Rated conditions Cooling : Indoor air temperature 27°C DB/19°C WB, Outdoor air temperature 35°C DB


Based on equivalent piping length of 7.5 m and piping height difference of 0 m.

*3 Be sure to refer to the Engineering Data book for details of those conditions and requirements.

Outdoor units external drawings

**Model : MMY-MAP0807T7P, MMY-MAP0807T8P
 MMY-MAP1007T7P, MMY-MAP1007T8P
 MMY-MAP1207T7P, MMY-MAP1207T8P
 MMY-MAP1407T7P, MMY-MAP1407T8P**

Model Name	φA	Model Name	φB
MMY-MAP0807 type	φ19.1	MMY-MAP0807 type	φ12.7
MMY-MAP1007 type	φ22.2	MMY-MAP1007 type	φ12.7
MMY-MAP1207 type	φ28.6	MMY-MAP1207 type	φ12.7
MMY-MAP1407 type	φ28.6	MMY-MAP1407 type	φ15.9




(Note)

1. IF there is an obstacle at the upper side of the outdoor unit, set the top end of the outdoor unit 2000mm apart from the obstacle
2. Limit the height of the obstacle surrounding the outdoor unit to 800mm or less from the bottom end of the outdoor unit.
3. Draw out the pipe procured locally to the front of the outdoor unit horizontally and keep 500mm or more between the outdoor unit and traversing pipe if placing pipe transversely.
4. Dimensional drawing of corrosion heavy protection model is the same as that of standard model.

(Unit:mm)

**Model : MMY-MAP14A7T8P, MMY-MAP14A7T7P
 MMY-MAP1607T8P, MMY-MAP1607T7P
 MMY-MAP1807T8P, MMY-MAP1807T7P
 MMY-MAP2007T8P, MMY-MAP2007T7P**





(Note)

1. IF there is an obstacle at the upper side of the outdoor unit, set the top end of the outdoor unit 2000mm apart from the obstacle
2. Limit the height of the obstacle surrounding the outdoor unit to 800mm or less from the bottom end of the outdoor unit.
3. Draw out the pipe procured locally to the front of the outdoor unit horizontally and keep 500mm or more between the outdoor unit and traversing pipe if placing pipe transversely.
4. Dimensional drawing of corrosion heavy protection model is the same as that of standard model.

(Unit:mm)

**Model : MMY-MAP2207T8P, MMY-MAP2207T7P
MMY-MAP2407T8P, MMY-MAP2407T7P**

Model Name	ΦA
MMY-MAP2207T8P	Φ28.6
MMY-MAP2407T8P	Φ34.9



Gas pipe connection port ϕA

Liquid pipe connection port 19.1

(Note)

1. If there is an obstacle at the upper side of the outdoor unit, set the top end of the outdoor unit 200mm apart from the obstacle.
2. Limit the height of the obstacle surrounding the outdoor unit to 800mm or less from the bottom end of the outdoor unit.
3. Draw out the pipe procured locally to the front of the outdoor unit horizontally, and keep 500mm or more between the outdoor unit and traversing pipe if placing pipe transversely.
4. Dimensional drawing of corrosion heavy protection model is the same as that of standard model.

(Unit:mm)





Indoor units

Cooling capacity (HP)	4-way air discharge cassette type (MMU-)	Compact 4-way cassette type (MMU-)	2-way air discharge cassette type (MMU-)	1-way air discharge cassette type (MMU-)	Slim duct type (MMD-)	Super Slim duct type (MMD-)	Concealed duct high static pressure type (MMD-)	Concealed duct type (MMD-)
2.2 kW (0.8 HP)		AP0077MH-E	AP0072WH1	AP0074YH1-E	AP0074SPH1-E	AP0076M(P)HY*		AP0076BHP1-E
2.5 kW (0.9HP)						AP0086M(P)HY*		
2.8 kW (1.0 HP)	AP0094HP1-E	AP0097MH-E	AP0092WH1	AP0094YH1-E	AP0094SPH1-E	AP0096M(P)HY*		AP0096BHP1-E
3.2kW (1.1HP)						AP0106M(P)HY*		
3.6 kW (1.25HP)	AP0124HP1-E	AP0127MH-E	AP0122WH1	AP0124YH1-E	AP0124SPH1-E	AP0126M(P)HY*		AP0126BHP1-E
4.0 kW (1.5HP)						AP0146M(P)HY*		
4.5 kW (1.7 HP)	AP0154HP1-E	AP0157MH-E	AP0152WH1	AP0154SH1-E	AP0154SPH1-E	AP0156M(P)HY*		AP0156BHP1-E
5.0 kW (1.85HP)						AP0176M(P)HY*		
5.6 kW (2.0 HP)	AP0184HP1-E	AP0187MH-E	AP0182WH1	AP0184SH1-E	AP0184SPH1-E	AP0186M(P)HY*	AP0186HP1-E	AP0186BHP1-E
6.3 kW (2.25HP)						AP0206M(P)HY*		
7.1 kW (2.5HP)	AP0244HP1-E		AP0242WH1	AP0244SH1-E	AP0244SPH1-E	AP0246M(P)HY*	AP0246HP1-E	AP0246BHP1-E
8.0 kW (3.0 HP)	AP0274HP1-E		AP0272WH1		AP0274SPH1-E	AP0276M(P)HY*	AP0276HP1-E	AP0276BHP1-E
9.0 kW (3.2 HP)	AP0304HP1-E		AP0302WH1					AP0306BHP1-E
11.2 kW (4.0 HP)	AP0364HP1-E		AP0362WH1				AP0366HP1-E	AP0366BHP1-E
14.0 kW (5.0 HP)	AP0484HP1-E		AP0482WH1				AP0486HP1-E	AP0486BHP1-E
16.0 kW (6.0 HP)	AP0564HP1-E		AP0562WH1				AP0566HP1-E	AP0566BHP1-E
22.4 kW (8.0 HP)							AP0726HP-E	
28.0 kW (10.0 HP)							AP0966HP-E	



Cooling capacity (HP)	Ceiling type (MMC-)	High wall type series 3 (MMK-)	High wall type Series 7 (MMK-)	Floor standing concealed type (MML-)	Floor standing cabinet type (MML-)	Console type (MML-)	Floor standing type (MMF-)	Large capacity floor standing Direct type (MMF-)	Large capacity floor standing Duct type (MMF-)
2.2 kW (0.8 HP)		AP0073H1	AP0077HP-E	AP0074BH1-E	AP0074H1-E	AP0074NH1-E			
2.8 kW (1.0 HP)		AP0093H1	AP0097HP-E	AP0094BH1-E	AP0094H1-E	AP0094NH1-E			
3.6 kW (1.25 HP)		AP0123H1	AP0127HP-E	AP0124BH1-E	AP0124H1-E	AP0124NH1-E			
4.5 kW (1.7 HP)	AP0158HP-E	AP0153H1		AP0154BH1-E	AP0154H1-E	AP0154NH1-E	AP0156H1-E		
5.6 kW (2.0 HP)	AP0188HP-E	AP0183H1		AP0184BH1-E	AP0184H1-E	AP0184NH1-E	AP0186H1-E		
7.1 kW (2.5 HP)	AP0248HP-E	AP0243H1		AP0244BH1-E	AP0244H1-E		AP0246H1-E		
8.0 kW (3.0 HP)	AP0278HP-E						AP0276H1-E		
11.2 kW (4.0 HP)	AP0368HP-E						AP0366H1-E		
14.0 kW (5.0 HP)	AP0488HP-E						AP0486H1-E		
16.0 kW (6.0 HP)	AP0568HP-E						AP0566H1-E		
22.4 kW (8.0 HP)								AP0724H-VA/VB**	AP0724DH-V
28.0 kW (10.0 HP)								AP0964H-VA/VB**	AP0964DH-V
45.0 kW (16.0 HP)								AP1444H-VA/VB**	AP1444DH-V
56.0 kW (20.0 HP)								AP1924H-VA/VB**	AP1924DH-V



Air volume	Fresh air intake indoor unit type (MMD-)	Air to air heat exchanger with DX coil (MMD-)
150 m ³ /h		
250 m ³ /h		
350 m ³ /h		
500 m ³ /h		VN502HEX1E
650 m ³ /h		
800 m ³ /h		VN802HEX1E
1000 m ³ /h		VN1002HEX1E / HEX1E2**
1500 m ³ /h		
2000 m ³ /h		
1080 m ³ /h	AP0481HFE	
1680 m ³ /h	AP0721HFE	
2100 m ³ /h	AP0961HFE	

Air to air heat exchanger***
VN-M150HE
VN-M250HE
VN-M350HE
VN-M500HE
VN-M650HE
VN-M800HE
VN-M1000HE
VN-M1500HE
VN-M2000HE

*Super slim duct MMD-AP***6MPHY, P means coming with drain pump.

** 60Hz (7P) Models Only

*** Do not connect to refrigerant piping from outdoor unit. Control wires can be connected.



4-way air discharge cassette type

MMU-AP***4HP1-E



Individual louver control

The angles of each of the four louver can be set individually
=> Enables airflow to be adapted to user preferences.

Easy installation

The panel is attached using the bolt already installed on the indoor unit.


(1) Standard swing




(2) Diagonally opposite swing



(3) Turn-around swing



Note: RBC-AMT32E, RBC-AMS41E only



RBC-U31PGP(W)-E

Technical specifications

Model name		MMU-	AP0094HP1-E	AP0124HP1-E	AP0154HP1-E	AP0184HP1-E	AP0244HP1-E	AP0274HP1-E	AP0304HP1-E	AP0364HP1-E	AP0484HP1-E	AP0564HP1-E	
Cooling capacity*1		(kW/Btu/h)	2.8 / 9,600	3.6 / 12,300	4.5 / 15,400	5.6 / 19,000	7.1 / 24,000	8.0 / 27,300	9.0 / 37,000	11.2 / 38,000	14.0 / 47,800	16.0 / 54,600	
Electrical characteristics	Power requirements	1-phase 50Hz 230V (220-240V) / 1-phase 60Hz 220V(208-230) (Separate power supply for indoor units required.)											
	Power consumption 50 Hz/60 Hz	(kW)	0.021/0.021	0.023/ 0.023	0.026/ 0.026	0.036/0.036	0.043/ 0.043	0.088/ 0.088	0.112/ 0.112	0.112/ 0.112	0.112/ 0.112	0.112/ 0.112	0.112/ 0.112
Appearance (Ceiling panel)		Model	RBC-U31PGP(W)-E										
External dimensions: Main unit (Ceiling panel)*	Height	(mm)	256 (30)*						319 (30)*				
	Width	(mm)	840 (950)*										
	Depth	(mm)	840 (950)*										
Total weight: Main unit (Ceiling panel)*		(kg)	18 (4)*		20 (4)*					25 (4)*			
Fan unit	Standard air flow (High/Mid/Low)	(m³/h)	800/730/680		930/ 830/790	1050/ 920/800	1290/920/800		1320/ 1110/850	1970/ 1430/1070	2130/ 1430/1130	2130/ 1520/1230	
	Motor output	(W)	14			20			68	72			
Connecting pipe	Gas side	(mm)	ø9.5		ø12.7			ø15.9					
	Liquid side	(mm)	ø6.4						ø9.5				
	Drain port (nominal dia.)	(mm)	25 (Polyvinyl chloride tube)										
Sound pressure level*2 (High/Mid/Low)		(dB(A))	30/29/27		31/29/27	32/29/27	35/31/28		38/33/30	43/38/32	46/38/33	46/40/33	

* Figures in parentheses are for ceiling panels.

Note 1 : The capacities are measured under the conditions specified by JIS B 8615 based on the reference piping.


The reference piping consists of 5 m of main piping and 2.5 m of branch piping connected with 0 m height.

Note 2 : The sound level are measured in an anechoic chamber in accordance with JIS B 8616.

Normally, the values measured in the actual operating environment become larger than the indicated values due to the effects of external sound.


Note : Rated conditions Cooling : Indoor air temperature 27°C DB/19°C WB, Outdoor air temperature 35°C DB

MMU-AP0074HP1-E to AP0564HP1-E



* The figure shows the RBC-U31PGP(W)-E panel.

Options




Compact 4-way cassette type

MMU-AP***7MH-E



Superior design with compact chassis

This compact unit (620 × 620 mm) fits with flat panel perfectly into ceilings and matches standard architectural modules without the need to cut ceiling tiles, makes your room look more elegant.



Individual louver control*

The wind direction and swing operation can be set individually by each louver, which can be set into memory for future use. Furthermore, the optional occupancy sensor also improve efficiency energy.



*The function is available with RBC-AMS55E-ES/EN



Technical specifications

Model name	MMU-	AP0077MH-E	AP0097MH-E	AP0127MH-E	AP0157MH-E	AP0187MH-E	
Cooling capacity*1	(kW/Btu/h)	2.2 / 7,500	2.8 / 9,600	3.6 / 12,300	4.5 / 15,400	5.6 / 19,000	
Electrical characteristics	Power requirements	1-phase 50Hz 230V (220-240V) / 1-phase 60Hz 220V (Separate power supply for indoor units required.)					
	Power consumption 50 Hz/60 Hz	(kW)	0.016/0.016	0.025/0.025	0.027/0.027	0.030/0.030	0.052/0.052
Appearance (Ceiling panel)	Model	RBC-UM21PG(W)-E					
External dimensions: Main unit (Ceiling panel)*	Height	(mm)	256 (12)*				
	Width	(mm)	575 (620)*				
	Depth	(mm)	575 (620)*				
Total weight: Main unit (Ceiling panel)*	(kg)	15 (2.5)*					
Fan unit	Standard air flow (M+ / M / L+ / L)	(m³/h)	552 (500/462/395/378)	570 (520/468/395/378)	594 (550/504/420/402)	660 (600/552/480/468)	840 (740/642/540/522)
	Motor output	(W)	60				
Connecting pipe	Gas side	(mm)	ø9.5		ø12.7		
	Liquid side	(mm)	ø6.4				
	Drain port (Nominal dia. mm)		VP 20 (Polyvinyl chloride tube)				
Sound pressure level*2 High (M+ / M / L+ / L)	(dB(A))	37 (34/33/30/29)	38 (35/33/30/29)	38 (36/34/31/30)	40 (37/35/32/31)	47 (43/39/36/34)	

* Figures in parentheses are for ceiling panels.

Note 1 : The capacities are measured under the conditions specified by JIS B 8615 based on the reference piping. The reference piping consists of 5 m of main piping and 2.5 m of branch piping connected with 0 m height.

Note 2 : The sound level are measured in an anechoic chamber in accordance with JIS B 8616.


Normally, the values measured in the actual operating environment become larger than the indicated values due to the effects of external sound.

Note: Rated conditions Cooling : Indoor air temperature 27°C DB/19°C WB, Outdoor air temperature 35°C DB


Heating : Indoor air temperature 20°C DB, Outdoor air temperature 7°C DB/6°C WB

Note: M+, L+ will be available with RBC-AMS55E-ES/EN only.

MMU-AP0077MH-E to AP0187MH-E



Options



2-way air discharge cassette type
MMU-AP*2WH1**

Slim and compact unit

Unified the width of ceiling panel to 680mm.

Condensate drain pump included.

Available for ceilings up to 3.8m in height. (in case of 0.8HP to 3.2HP)

Easy installation and fine adjustment using the "Adjust-Cover" function.

Technical specifications

Model name		MMU-	AP0072WH1	AP0092WH1	AP0122WH1	AP0152WH1	AP0182WH1	AP0242WH1	AP0272WH1	AP0302WH1	AP0362WH1	AP0482WH1	AP0562WH1		
Cooling capacity*1		(kW/Btu/h)	2.2/7,500	2.8/9,600	3.6/12,300	4.5/15,400	5.6/19,000	7.1/24,000	8.0/27,300	9.0/37,000	11.2/38,000	14.0/47,800	16.0/54,600		
Electrical characteristics	Power requirements	1-phase 50Hz 230V (220~240V) / 1-phase 60Hz 220V (Separate power supply for indoor units required.)													
	Power consumption 50 Hz/60 Hz	(kW)	0.029/0.029			0.030/0.030	0.044/0.044	0.054/0.054		0.064/0.064	0.076/0.076	0.088/0.088	0.117/0.117		
Appearance (Ceiling panel)	Model	RBC-UW283PG(W)-E				RBC-UW803PG(W)-E				RBC-UW1403(W)PG-E					
External dimensions: Main unit (Ceiling panel)*	Height	(mm)	295 (20)				345 (20)								
	Width	(mm)	815 (1050)				1180 (1415)				1600 (1835)				
	Depth	(mm)	570 (680)												
Total weight: Main unit (Ceiling panel)*		(kg)	19 (10)				26 (14)				36 (14)				
Fan unit	Standard air flow (High/Mid/Low)	(m ³ /h)	558/498/450		600/534/450	900/750/618	1050/840/738		1260/900/780	1740/1434/1182	1800/1482/1230	2040/1578/1320			
	Motor output	(W)	20			30		40		50		70			
Connecting pipe	Gas side	(mm)	ø9.5		ø12.7		ø15.9								
	Liquid side	(mm)	ø6.4				ø9.5								
	Drain port	(nominal dia.)	25 (Polyvinyl chloride tube)												
Sound pressure level*2 (High/Mid/Low)		(dB(A))	34/32/30		35/33/30		38/35/33		40/37/34		42/39/36		43/40/37		46/42/39

* Figures in parentheses are for ceiling panels.

Note 1 : The capacities are measured under the conditions specified by JIS B 8615 based on the reference piping.


The reference piping consists of 5 m of main piping and 2.5 m of branch piping connected with 0 m height.

Note 2 : The sound level are measured in an anechoic chamber in accordance with JIS B 8616.


Normally, the values measured in the actual operating environment become larger than the indicated values due to the effects of external sound.

Note : Rated conditions Cooling : Indoor air temperature 27°C DB/19°C WB, Outdoor air temperature 35°C DB


MMU-AP0072WH1 to AP0152WH1




MMU-AP0182WH1 to AP0302WH1



MMU-AP0362WH1 to AP0562WH1



Options



1-way air discharge cassette type

MMU-AP***4YH1-E
MMU-AP***4SH1-E



◀ The perfect choice for hotels and reception areas

Silent sound design ensures the quiet required for the office. Ideal for smaller rooms where one-way air distribution is required. Able to blow air straight out. Condensate drain pump included. Long-life filters fitted as standard.

◀ Fresh air intake is possible (MMU-AP***4SH1-E)

Preparations/connection possible with a circle duct flange.

Technical specifications

Model name	MMU-	AP0074YH1-E	AP0094YH1-E	AP0124YH1-E	AP0154SH1-E	AP0184SH1-E	AP0244SH1-E
Cooling capacity*1	(kW/Btu/h)	2.2 / 7,500	2.8 / 9,600	3.6 / 12,300	4.5 / 15,400	5.6 / 19,000	7.1 / 24,000
Electrical characteristics	Power requirements	1-phase 50Hz 230V (220–240V) / 1-phase 60Hz 220V (Separate power supply for indoor units required.)					
	Power consumption 50 Hz/60 Hz (kW)		0.053/0.056		0.042/0.041	0.046/0.045	0.075/0.073
Appearance (Ceiling panel)	Model		RBC-UY136PG			RBC-US21PGE	
External dimensions: Main unit (Ceiling panel)*	Height (mm)		235 (18)*			200 (20)*	
	Width (mm)		850 (1050)*			1000 (1230)*	
	Depth (mm)		400 (470)*			710 (800)*	
Total weight: Main unit (Ceiling panel)*	(kg)		22 (3.5)*			21 (5.5)*	22 (5.5)*
Fan unit	Standard air flow (High/Mid/Low) (m ³ /h)		540/480/420		750/690/630	780/720/660	1140/960/810
	Motor output (W)		22			30	
Connecting pipe	Gas side (mm)		ø9.5			ø12.7	ø15.9
	Liquid side (mm)			ø6.4			ø9.5
	Drain port (nominal dia.)				25 (Polyvinyl chloride tube)		
Sound pressure level*2 (High/Mid/Low)	(dB(A))		42/39/34		37/35/32	38/36/34	45/41/37

* Figures in parentheses are for ceiling panels.

Note 1 : The capacities are measured under the conditions specified by JIS B 8615 based on the reference piping.


The reference piping consists of 5 m of main piping and 2.5 m of branch piping connected with 0 m height.

Note 2 : The sound level are measured in an anechoic chamber in accordance with JIS B 8616.


Normally, the values measured in the actual operating environment become larger than the indicated values due to the effects of external sound.

Note : Rated conditions Cooling : Indoor air temperature 27°C DB/19°C WB, Outdoor air temperature 35°C DB

MMU-AP0074YH1-E to AP0124YH1-E





MMU-AP0154SH1-E to AP0244SH1-E




Options

MMU-AP0074YH1-E/AP0094YH1-E/AP0124YH1-E



MMU-AP0154SH1-E/AP0184SH1-E/AP0244SH1-E



Slim duct type

MMD-AP***4SPH1-E

◀ Functional design

Only 210 mm in height for greater application flexibility. 4-step static pressure setup. Concealed installation within a ceiling void. Auxiliary fresh air intake available

◀ Slim & quiet

Perfect comfort throughout the room. Can be used with any style of air diffuser. Quiet, powerful operation.

Technical specifications

Model name		MMD-	AP0074SPH1-E	AP0094SPH1-E	AP0124SPH1-E	AP0154SPH1-E	AP0184SPH1-E	AP0244SPH1-E	AP0274SPH1-E	
Cooling capacity*1		(kW/Btu/h)	2.2 / 7,500	2.8 / 9,600	3.6 / 12,300	4.5 / 15,400	5.6 / 19,000	7.1 / 24,000	8.0 / 27,300	
Electrical characteristics	Power requirements	1-phase 50Hz 230V (220-240V) / 1-phase 60Hz 220V (Separate power supply for indoor units required.)								
	Power consumption 50 Hz/60 Hz	(kW)	0.039/0.037		0.043/0.041	0.045/0.043	0.054/0.052	0.105//0.105		
External dimensions	Height	(mm)	210							
	Width	(mm)	845					1140		
	Depth	(mm)	645							
Total weight		(kg)	22			23		29		
Fan unit	Standard air flow (High/Mid/Low)	(m ³ /h)	540/470/400		600/520/450	690/600/520	780/680/580	1080/1000/900		
	Motor output	(W)	60							
	External static pressure	(Pa)	6-16-31-46 (4 steps)		5-15-30-45 (4 steps)		4-14-29-44 (4 steps)	2-12-22-42 (4 steps)		
Connecting pipe	Gas side	(mm)	ø9.5			ø12.7		ø15.9		
	Liquid side	(mm)	ø6.4							
	Drain port	(nominal dia.)	25 (Polyvinyl chloride tube)							
Sound pressure level*2 (High/Med./Low)	Under air inlet	(dB(A))	36/33/30	38/35/32	39/36/33	40/38/36	49/47/44			
	Back air inlet	(dB(A))	28/26/24	29/27/25	32/30/28	33/31/29	38/36/33			

Note 1 : The capacities are measured under the conditions specified by JIS B 8615 based on the reference piping.


The reference piping consists of 5 m of main piping and 2.5 m of branch piping connected with 0 m height.

Note 2 : The sound level are measured in an anechoic chamber in accordance with JIS B 8616.




Normally, the values measured in the actual operating environment become larger than the indicated values due to the effects of external sound.

Note : Rated conditions Cooling : Indoor air temperature 27°C DB/19°C WB, Outdoor air temperature 35°C DB


MMD-AP0074SPH1-E to AP0184SPH1-E







● Space required for installation and servicing



MMD-AP0244SPH1-E to AP0274SPH1-E




● Space required for installation and servicing



Options

Auxiliary fresh air flange
TCB-FF101URE2



Super slim duct type


MMD-AP***6MPHY
MMD-AP***6MHY(*3)




Features

- Very compact design: Only 21 cm height & 45 cm depth
- Wide range choice (12 capacities)
- Easy maintenance - external electrical box
- Choice with high-lift drain pump (350 mm) MPHY or without drain pump MHY(*3)

MMD-AP***6MPHY/MMD-AP***6MHY*



Space required for installation and servicing



* Standard filter needs to be purchased locally.

Technical specifications

Model name	MMD-	AP0076MPHY AP0076MHY(*3)	AP0086MPHY AP0086MHY(*3)	AP0096MPHY AP0096MHY(*3)	AP0106MPHY AP0106MHY(*3)	AP0126MPHY AP0126MHY(*3)	AP0146MPHY AP0146MHY(*3)	AP0156MPHY AP0156MHY(*3)	AP0176MPHY AP0176MHY(*3)	AP0186MPHY AP0186MHY(*3)	AP0206MPHY AP0206MHY(*3)	AP0246MPHY AP0246MHY(*3)	AP0276MPHY AP0276MHY(*3)		
Cooling capacity*1	(kW/Btu/h)	2.2/7,500	2.5/8,600	2.8/9,600	3.2/11,000	3.6/12,300	4.0/13,700	4.5/15,400	5.0/17,100	5.6/19,000	6.3/21,500	7.1/24,000	8.0/27,300		
Electrical characteristics	Power requirements	1-phase 50Hz 230V (220~240V) / 1-phase 60Hz 220V (Separate power supply for indoor units required.)													
	Power consumption (AP***MPHY/AP***MHY)	kW	0.052/ 0.048	0.052/ 0.048	0.052/ 0.048	0.052/ 0.048	0.058/ 0.054	0.058/ 0.054	0.066/ 0.062	0.066/ 0.062	0.066/ 0.062	0.069/ 0.065	0.076/ 0.072	0.076/ 0.072	
External dimensions	Height	mm	210												
	Width	mm	700					900				1100			
	Depth	mm	450												
Total weight	kg	19					22				25				
Fan unit	Standard air flow (High/Mid/Low)	m ³ /h	570/475/380				610/500/385			780/580/420			1000/ 870/740	1060/910/760	
	Motor output	W	95												
	External static pressure	Pa	10-20-35-45 (4 steps)												
Connecting pipe	Gas side	mm	ø9.5					ø12.7				ø15.9			
	Liquid side	mm	ø6.4												
	Drain port (nominal dia.)	mm	25 (Polyvinyl chloride tube)												
Sound pressure level*2 (High/Mid/Low)	Under air inlet	dB(A)	41/35/30				43/36/30			41/34/27			43/40/37	45/41/38	
	Back air inlet	dB(A)	33/29/25				35/29/25			33/27/22			37/33/30	38/34/31	

Note 1 : The capacities are measured under the conditions specified by JIS B 8615 based on the reference piping. The reference piping consists of 5 m of main piping and 2.5 m of branch piping connected with 0 m height.

Note 2 : The sound level are measured in an anechoic chamber in accordance with JIS B 8616.

Normally, the values measured in the actual operating environment become larger than the indicated values due to the effects of external sound.

Note : Rated conditions Cooling : Indoor air temperature 27°C DB/19°C WB, Outdoor air temperature 35°C DB

Note 3 : Without drain pump



SMMS -7 VRF

Air Conditioning for large building.



Concealed duct high static pressure type



MMD-AP***6HP1-E



MMD-AP***6HP-E

Design flexibility

Satisfies all your design needs.
Compatible with external static pressures up to 250 Pa.

Can be equipped with the following options:

- Long life filter kit
- Drain pump kit

Construction characteristics

Seven-stage-switchable static pressure.
The flexible duct is accessible.
Easy service and installation.
Inspection hole enables easy access and maintenance.

*Built-in Drain-pump : up to 6 HP model

Technical specifications


Model name	MMD-	AP0186HP1-E	AP0246HP1-E	AP0276HP1-E	AP0366HP1-E	AP0486HP1-E	AP0566HP1-E	AP0726HP-E	AP0966HP-E	
Cooling capacity*1	(kW/Btu/h)	5.6 / 19,000	7.1 / 24,000	8.0 / 27,300	11.2 / 38,000	14.0 / 47,800	16.0 / 54,600	22.4 / 78,500	28.0 / 98,300	
Electrical characteristics	Power requirements	1-phase 50Hz 230V (220-240V) / 1-phase 60Hz 220V (208V-230V) (Separate power supply for indoor units required.)								
	Power consumption 50 Hz/60 Hz	(kW)	0.085/0.085	0.115/0.115	0.198/0.198	0.230/0.230	0.290/0.290	0.540/0.540	0.790/0.790	
External dimensions	Height	(mm)	298						448	
	Width	(mm)	1,000			1,400			1,400	
	Depth	(mm)	750						900	
Total weight	(kg)	34			43			97		
Fan unit	Standard air flow (Med./Low)	(m ³ /h)	800 (660/550)	1,200 (970/800)	1,920 (1,560/1,340)	2,100 (1,740/1,420)	2,400 (2,040/1,660)	3,800 (3,200/2,500)	4,800 (4,200/3,500)	
	Motor output	(W)	250			350			250	
	External static pressure (factory setting)	(Pa)	100						150	
	External static pressure	(Pa)	50-75-125-150-175-200 (7steps)						50-83-117-150-183-217-250 (7steps)	
Connecting pipe	Gas side	(mm)	ø12.7			ø15.9			ø22.2	
	Liquid side	(mm)	ø6.4			ø9.5			ø12.7	
	Drain port	(nominal dia.)	25 (Polyvinyl chloride tube)						25 (Polyvinyl chloride tube)	
Sound pressure level*2 (High/Mid/Low)	(dB(A))	37 (32/30)	38 (34/31)	41 (37/34)	42 (40/35)	45 (42/37)	44 (40/36)	46 (42/38)		

Note 1 : The cooling capacities and electrical characteristics are measured under the conditions specified by JIS B 8615 based on the reference piping. The reference piping consists of 5m of main piping and 2.5 of branch piping connected with 0 meter height.

Note 2 : The sound level are measured in an anechoic chamber in accordance with JIS B 8616.

Normally, the values measured in the actual operating environment become larger than the indicated values due to the effects of external sound.

Note : Rated conditions Cooling : Indoor air temperature 27°C DB/19°C WB, Outdoor air temperature 35°C DB

Concealed duct type
MMD-AP*6BHP1-E**

High static pressure

External static pressure can be raised as high as 120 Pa, so that all areas of the room can be reached for even temperature distribution, no matter how complex the layout.

High-lift drain pump

Built-in high-lift drain pump up to 850 mm.

Technical specifications

Model name	MMD-	AP0076BHP1-E	AP0096BHP1-E	AP0126BHP1-E	AP0156BHP1-E	AP0186BHP1-E	AP0246BHP1-E	AP0276BHP1-E	AP0306BHP1-E	AP0366BHP1-E	AP0486BHP1-E	AP0566BHP1-E	
Cooling capacity*1	(kW/Btu/h)	2.2/7,500	2.8/9,600	3.6/12,300	4.5/15,400	5.6/19,000	7.1/24,000	8.0/27,300	9.0/37,000	11.2/38,000	14.0/47,800	16.0/54,600	
Electrical characteristics	Power requirements	1-phase 50Hz 230V (220-240V) / 1-phase 60Hz 220V (208V-230V) (Separate power supply for indoor units required.)											
	Power consumption 50 Hz/60 Hz (kW)	0.038/0.038	0.043/0.043		0.062/0.062		0.077/0.077		0.094/0.094	0.172/0.172		0.198/0.198	
External dimension	Height (mm)	275											
	Width (mm)	700			700			1,000			1,400		
	Depth (mm)	750											
Total weight (kg)		23					30			40			
Fan unit	Standard air flow (Mid/Low) (m ³ /h)	540/450/360	570/480/390		798/660/540		1,200/990/870		1,260/1,110/930	1,920/1,620/1,380		2,100/1,740/1,500	
	Motor output (W)	150					250						
	External static pressure (factory setting) (Pa)	30					40			50			
	External static pressure (Pa)	30-40-50-65-80-100-120 (7 steps)											
Connecting pipe	Gas side (mm)	ø9.5			ø12.7			ø15.9					
	Liquid side (mm)	ø6.4						ø9.5					
	Drain port dia. (nominal)	25 (Polypropylene tube)											
Sound pressure level*2 (High/Mid/Low) (dB(A))		29/26/23	30/26/23		33/29/25		36/31/27				40/36/33		

Note 1 : The capacities are measured under the conditions specified by JIS B 8615 based on the reference piping.


The reference piping consists of 5 m of main piping and 2.5 m of branch piping connected with 0 m height.

Note 2 : The sound level are measured in an anechoic chamber in accordance with JIS B 8616.

Normally, the values measured in the actual operating environment become larger than the indicated values due to the effects of external sound.

Note : Rated conditions Cooling : Indoor air temperature 27°C DB/19°C WB, Outdoor air temperature 35°C DB

MMD-AP0076BHP1-E to AP0566BHP1-E




* Standard filter is provided, but deeper filtration filter needs to be purchased locally.

Options

Spigot shaped flange

- TCB-SF56C6BPE
- TCB-SF80C6BPE
- TCB-SF160C6BPE





Ceiling type

MMC-AP*8HP-E**

◀ **Smooth curve for pliant shape**


All-new chassis and new rounded design, This new models have been developed in response to customers' needs for ceiling units that better match their room interiors.

New fan has adopted the turbulence prevention rib to optimize the ventilating way.

Air volume has increased and noise level also has decreased compared with previous model. Winds of new ceiling type of 4HP to 6HP can be reached up to 4.3 metre

◀ **New designed wide flap**

The new air outlet has realized both high noise reduction and large air volume.



◀ **Flap control**

The airflow angle is automatically set to the most suitable setting according to your cooling needs, and an automatic swing mode enables airflow to reach all areas of the room to create a comfortable ambience.

Technical specifications

Model name	MMC-	AP0158HP-E	AP0188HP-E	AP0248HP-E	AP0278HP-E	AP0368HP-E	AP0488HP-E	AP0568HP-E
Cooling capacity*1	(kW/Btu/h)	4.5 / 15,400	5.6 / 19,000	7.1 / 24,000	8.0 / 27,300	11.2 / 38,000	14.0 / 47,800	16.0 / 54,600
Electrical characteristics	Power requirements	1-phase 50Hz 230V (220-240V) / 1-phase 60Hz 220V (208V-230V) (Separate power supply for indoor units required.)						
	Power consumption 50 Hz/60 Hz (kW)	0.033/0.033	0.034/0.034	0.067/0.067		0.083/0.083		0.111/0.111
External dimensions	Height (mm)	235						
	Width (mm)	950		1,269		1,586		
	Depth (mm)	690						
Total weight (kg)		24		30		37		
Fan unit	Standard air flow (High/Mid/Low) (m ³ /h)	840 / 690/540	960 / 720/540	1440 / 1020/750		1860 / 1350/1020	1860 / 1530/1200	2040 / 1650/1260
	Motor (W)	94		94		139		
Connecting pipe	Gas side (mm)	ø12.7		ø15.9				
	Liquid side (mm)	ø6.4		ø9.5				
	Drain port (nominal dia.)	20 (Polyvinyl chloride tube)						
Sound pressure level*2 (High/Mid/Low) (dB(A))		36/34/28	37/35/28	41/36/29		44/38/32	44/41/35	46/42/36





Note 1 : The capacities are measured under the conditions specified by JIS B 8615 based on the reference piping.

The reference piping consists of 5 m of main piping and 2.5 m of branch piping connected with 0 m height.


Note 2 : The sound level are measured in an anechoic chamber in accordance with JIS B 8616.

Normally, the values measured in the actual operating environment become larger than the indicated values due to the effects of external sound.


Note : Rated conditions Cooling : Indoor air temperature 27°C DB/19°C WB, Outdoor air temperature 35°C DB



Wireless sensor mounting section




● Space required for installation and servicing



Model	MMC-	A	B
AP0158HP-E, AP0188HP-E		906	950
AP0248HP-E, AP0278HP-E		1,223	1,270
AP0368HP-E, AP0488HP-E, AP0568HP-E		1,540	1,586


(Unit: mm)

Options



High-wall type (series 3)

MMK-AP***3H1



Elegant and slim

This classic high-wall is elegant and slim; it can easily blend in with any room interior.



Total comfort is granted, thanks also to the 70° directional auto-swing louver that provides uniform air distribution.



Remote controller

* Wireless remote controller is packed with indoor unit.

MMK-AP0073H1 to AP0243H1



(Unit: mm)

Technical specifications

Model name		MMK-	AP0073H1	AP0093H1	AP0123H1	AP0153H1	AP0183H1	AP0243H1
Cooling capacity*1		(kW/Btu/h)	2.2 / 7,500	2.8 / 9,600	3.6 / 12,300	4.5 / 15,400	5.6 / 19,000	7.1 / 24,000
Electrical characteristics	Power requirements	1-phase 50Hz 230V (220-240V) / 1-phase 60Hz 220V (208V-230V) (Separate power supply for indoor units required.)						
	Power consumption 50 Hz/60 Hz	(kW)	0.018/0.018	0.021/0.021		0.043/0.043		0.050/0.050
External dimensions	Height	(mm)	320					
	Width	(mm)	1050					
	Depth	(mm)	228					
Total weight		(kg)	15					
Fan unit	Standard air flow (High/Mid/Low)	(m ³ /h)	570/450/390	600/480/390		840/660/540		1020/750/570
	Motor output	(W)	30					
Connecting pipe	Gas side	(mm)	ø9.5		ø12.7		ø15.9	
	Liquid side	(mm)	ø6.4					
	Drain port	(nominal dia.)	16 (polyvinyl chloride tube)					
Sound pressure level*2 (High/Mid/Low)		(dB(A))	35/31/28	37/32/28		41/36/33		46/39/34

Note 1 : The capacities are measured under the conditions specified by JIS B 8615 based on the reference piping.

The reference piping consists of 5 m of main piping and 2.5 m of branch piping connected with 0 m height.


Note 2 : The sound level are measured in an anechoic chamber in accordance with JIS B 8616.

Normally, the values measured in the actual operating environment become larger than the indicated values due to the effects of external sound.

Note : Rated conditions Cooling : Indoor air temperature 27°C DB/19°C WB, Outdoor air temperature 35°C DB

High wall type (series 7)

MMK-AP***7HP-E



Compact and aesthetic design


Glossy material, smooth, curve and white LED are designed to reflect luxurious appearance and to complement modern exterior beautifully.



Remote controller

* Wireless remote controller is packed with indoor unit.

MMK-AP0077HP-E to MMK-AP0127HP-E



Technical specifications

Model name	MMK-	AP0077HP-E	AP0097HP-E	AP0127HP-E	
Cooling Capacity ¹	(kW/Btu/h)	2.2 / 7,500	2.8 / 9,600	3.6 / 12,300	
Electrical characteristics	Power requirements	1-phase 50Hz 230V (220-240V) / 1-phase 60Hz 220V (208V-230V) (Separate power supply for indoor units required.)			
	Power consumption 50 Hz	(kW)	0.015	0.016	0.017
External dimensions	Height	(mm)	293		
	Width	(mm)	798		
	Depth	(mm)	230		
Total weight	(kg)	11			
Fan unit	Standard air flow (High/Mid/Low)	(m ³ /h)	480/385/270	510/395/270	540/410/300
	Motor output	(W)	30		
Connecting pipe	Gas side	(mm)	Ø9.5		
	Liquid side	(mm)	Ø6.4		
	Drain port	(nominal dia. mm)	16 (Polyvinyl chloride tube)		
Sound pressure level ² (High/Mid/Low)	(dB(A))	35/30/25	36/31/25	37/32/25	

Note 1 : The capacities are measured under the conditions specified by JIS B 8615 based on the reference piping. The reference piping consists of 5 m of main piping and 2.5 m of branch piping connected with 0 m height.


Note 2 : The sound level are measured in an anechoic chamber in accordance with JIS B 8616.

Normally, the values measured in the actual operating environment become larger than the indicated values due to the effects of external sound.

Note : Rated conditions Cooling : Indoor air temperature 27°C DB/19°C WB, Outdoor air temperature 35°C DB

High wall type (series 7)

MMK-AP***7HP-E



Compact and aesthetic design


Glossy material, smooth, curve and white LED are designed to reflect luxurious appearance and to complement modern exterior beautifully.



Remote controller

* Wireless remote controller is packed with indoor unit.

MMK-AP0157HP-ID to MMK-AP0247HP-ID



Technical specifications

Model name			MMK-AP0157HP-E1/TR1	MMK-AP0187HP-E1/TR1	MMK-AP0247HP-E1/TR1
Cooling capacity		(*) kW/Btu/h	4.5 / 15,400	5.6 / 19,000	7.1 / 24,000
Heating capacity		(*) kW/Btu/h	5.0	6.3	8.0
Electrical Characteristic			1 phase / 50Hz / 230V(220V-240V), 1 phase / 60 Hz / (208V-230V) (Separate power supply for indoor units is required.)		
		Power supply			
		Running current	A	0.25	0.28
		Power consumption	kW	0.028	0.032
		Starting current	A	0.35	0.38
Outer dimension		Height	mm	320	320
		Width	mm	1050	1050
		Depth	mm	250	250
Weight		kg		16	16
Air Flow (H / M+ / M / L+ / L)		m ³ /h	840/770/690/620/550	900/810/720/640/550	1200/1050/900/750/600
Sound Pressure Level (H / M+ / M / L+ / L) (*2)		dB(A)	40/38/36/34/32	41/39/37/35/32	45/42/39/36/33
Heat exchanger			Finned tube		
Soundproof/Heat-insulating material			Non-flammable insulation		
Fan			Cross Flow Fan		
Controller (Packed with unit)			WH-TA09NE		
Connecting pipe		Gas side	mm	φ 6.35	φ 9.53
		Liquid side	mm	φ 12.7	φ 15.88
Drain port diameter		mm	16 (Polyvinyl chloride tube)		


(*1) The cooling capacities and electrical characteristics are measured under the conditions specified by JIS B 8615 based on the reference piping. The reference piping consists of 5m of main piping and 2.5m of branch piping connected with 0 meter height.
 (*2) The sound level are measured in an anechoic chamber in accordance with JIS B 8616.
 Normally, the values measured in the actual operating environment become larger than the indicated values due to the effects of external sound.
 Note: Rated conditions Cooling: Indoor air temperature 27°C DB/19°C WB, Outdoor air temperature 35°C DB
 Heating: Indoor air temperature 20°C DB, Outdoor air temperature 7°C DB/6°C WB




Floor standing concealed type

MML-AP*4BH1-E**

- ◀ **Cool air makes for a pleasant indoor environment**
Install it under a window and air-condition any room effectively.
- ◀ **Easy maintenance**
Simplified design of fan and drainage pipe eases maintenance.



MML-AP0074BH1-E to AP0244BH1-E



Technical specifications

Model name	MML-	AP0074BH1-E	AP0094BH1-E	AP0124BH1-E	AP0154BH1-E	AP0184BH1-E	AP0244BH1-E	
Cooling capacity*1	(kW/Btu/h)	2.2 / 7,500	2.8 / 9,600	3.6 / 12,300	4.5 / 15,400	5.6 / 19,000	7.1 / 24,000	
Electrical characteristics	Power requirements	1-phase 50Hz 230V (220-240V) / 1-phase 60Hz 220V (Separate power supply for indoor units required.)						
	Power consumption 50 Hz/60 Hz	0.056/0.058		0.090/0.096		0.095/0.110		
External dimensions	Height	600						
	Width	74				045		
	Depth	220						
Total weight	(kg)	21				29		
Fan unit	Standard air flow (High/Mid/Low)	460/400/300			740/600/490		950/790/640	
	Motor output	19			70			
Connecting pipe	Gas side	φ9.5			φ12.7		φ15.9	
	Liquid side	φ6.4						
	Drain port	20 (Polyvinyl chloride tube)						
Sound pressure level** (High/Mid/Low)	(dB(A))	36/34/3				2/37/33		

Note 1 : The capacities are measured under the conditions specified by JIS B 8615 based on the reference piping.
The reference piping consists of 5 m of main piping and 2.5 m of branch piping connected with 0 m height.

Note 2 : The sound level are measured in an anechoic chamber in accordance with JIS B 8616.
Normally, the values measured in the actual operating environment become larger than the indicated values due to the effects of external sound.

Note : Rated conditions Cooling : Indoor air temperature 27°C DB/19°C WB, Outdoor air temperature 35°C DB

Floor standing cabinet type


MML-AP***4H1-E



Slim & compact design

Under-window mounting does not block lighting.
Indoor unit size of 2.2 kW to 7.1 kW is the same.
Distribution can be reversed to suit occupant preference.


Air blow from front panel
(factory default)



Air blow from top



MML-AP0074H1-E to AP0244H1-E



Technical specifications

Model name	MML-	AP0074H1-E	AP0094H1-E	AP0124H1-E	AP0154H1-E	AP0184H1-E	AP0244H1-E
Cooling capacity*1	(kW/Btu/h)	2.2 / 7,500	2.8 / 9,600	3.6 / 12,300	4.5 / 15,400	5.6 / 19,000	7.1 / 24,000
Electrical characteristics	Power requirements	1-phase 50Hz 230V (220-240V) / 1-phase 60Hz 220V (Separate power supply for indoor units required.)					
	Power consumption 50 Hz/60 Hz (kW)	0.056/0.053			0.092/0.092		0.102/0.113
External dimensions	Height (mm)	630					
	Width (mm)	950					
	Depth (mm)	230					
Total weight (kg)		37				40	
Fan unit	Standard air flow (High/Mid/Low) (m ³ /h)	480/420/360			900/780/650		1080/930/780
	Motor output (W)	45			70		
Connecting pipe	Gas side (mm)	ø9.5			ø12.7		ø15.9
	Liquid side (mm)	ø6.4			ø9.5		
	Drain port (nominal dia.)	20 (Polyvinyl chloride tube)					
Sound pressure level*2 (High/Mid/Low) (dB(A))		39/37/35			45/41/38		49/44/39

Note 1: The capacities are measured under the conditions specified by JIS B 8615 based on the reference piping.

The reference piping consists of 5 m of main piping and 2.5 m of branch piping connected with 0 m height.

Note 2: The sound level are measured in an anechoic chamber in accordance with JIS B 8616.

Normally, the values measured in the actual operating environment become larger than the indicated values due to the effects of external sound.

Note: Rated conditions Cooling: Indoor air temperature 27°C DB/19°C WB, Outdoor air temperature 35°C DB



Console type
MML-AP*4NH1-E**

Elegant & simple design


Elegant & simple design makes this unit a perfect fit for shops, office buildings, and luxury apartments. Multi-function operation is convenient, making adjustments by the user possible using the wireless remote controller.



Remote controller

* Wireless remote controller is packed with indoor unit.

MML-AP0074NH1-E to AP0184NH1-E



(Unit: mm)

Technical specifications

Model name	MML-	AP0074NH1-E	AP0094NH1-E	AP0124NH1-E	AP0154NH1-E	AP0184NH1-E
Cooling capacity*1	(kW/Btu/h)	2.2 / 7,500	2.8 / 9,600	3.6 / 12,300	4.5 / 15,400	5.6 / 19,000
Electrical characteristics	Power requirements	1-phase 50Hz 230V (220-240V) / 1-phase 60Hz 220V (208V-230V) (Separate power supply for indoor units required.)				
	Power consumption 50 Hz/60 Hz	(kW)	0.021/0.021	0.025/0.025	0.034/0.034	0.052/0.052
External dimensions	Height	(mm)	600			
	Width	(mm)	700			
	Depth	(mm)	220			
Total weight	(kg)	17				
Fan unit	Standard air flow (High/Mid/Low)	(m ³ /h)	510/366/282	552/408/324	624/468/384	726/528/426
	Motor output	(W)	41			
Connecting pipe	Gas side	(mm)	ø9.5		ø12.7	
	Liquid side	(mm)	ø6.4			
	Drain port	(nominal dia.)	16 (Polyvinyl chloride tube)			
Sound pressure level*2	(dB(A))	38/32/26	40/34/29	43/37/31	47/40/34	

Note 1 : The capacities are measured under the conditions specified by JIS B 8615 based on the reference piping.

The reference piping consists of 5 m of main piping and 2.5 m of branch piping connected with 0 m height.

Note 2 : The sound level are measured in an anechoic chamber in accordance with JIS B 8616.

Normally, the values measured in the actual operating environment become larger than the indicated values due to the effects of external sound.

Note : Rated conditions Cooling : Indoor air temperature 27°C DB/19°C WB, Outdoor air temperature 35°C DB

Large capacity floor standing

MMF-AP_5(D)HP-VA/VB



This system is particularly suitable to large rooms air condition like warehouse, factory and shopping mall.

CAPACITY



8 HP ~ 20 HP

AIR FLOW



Up to 3,600m³/h ~ 8,400m³/h

SOUND PRESSURE LEVEL



59 dB(A)

LOCAL CONTROLS



RBC-AXU31-E



RBC-ASCU11-E
RBC-AMTU31-E
RBC-AMSU51-ENES


Features

Model name	MMF-	Ducted Type				Direct Blow Type				
		AP0725DHP-VA	AP0965DHP-VA	AP1445DHP-VA	AP1925DHP-VA	AP0725HP-VA	AP0965HP-VA	AP1445HP-VA	AP1925HP-VA	
		AP0725DHP-VB	AP0965DHP-VB	AP1445DHP-VB	AP1925DHP-VB	AP0725HP-VB	AP0965HP-VB	AP1445HP-VB	AP1925HP-VB	
Capacity code	HP	8	10	16	20	8	10	16	20	
Cooling capacity	kW	22.4	28.0	45.0	56.0	22.4	28.0	45.0	56.0	
Electrical characteristics	Power supply	VA: 3 phase 50Hz 380-415V / VB: 3 phase 60Hz 380V								
	Running current (50Hz/60Hz)	A	1.68/1.69	2.85/2.74	4.26/4.16	5.67/5.18	1.42/1.29	2.27/1.94	2.91/2.54	3.77/3.49
	Power consumption (50Hz/60Hz)	kW	0.83/0.93	1.35/1.48	2.30/2.41	2.67/2.80	0.62/0.67	0.80/0.86	1.28/1.31	1.96/1.98
	Starting current (50Hz/60Hz)	A	9.4/8.2	19.6/17.7	31.5/27.0	45.6/42.0	9.4/8.2	19.6/17.7	31.5/27.0	31.5/27.0
Appearance		Cream (5Y 7/1.5)								
Dimensions (HxWxD)	mm	1820x890x540		1870x1300x760		2130x890x540		2280x1300x760		
Total weight	kg	150	155	280	290	170	175	320		
Heat exchanger		Copper tubes, Aluminum plate fins								
Soundproof / Heat-insulating material		Polyolefin form								
Fan unit	Fan	Multi blades centrifugal; Belt drive								
	Standard air flow	m ³ /h	3600	4500	7200	8400	3600	4200	7200	8400
	Air flow limit (Lower/Upper)	m ³ /h	2880/4320	3360/5040	5760/8640	6720/10080	2880/4320	3360/5040	5760/8640	6720/10080
	External static pressure	Pa	200	300	300	300	-	-	-	-
Sound pressure level	dB(A)	59	64	66	68	60	64	63	66	
Air filter		Standard filter supplied (Simple filter)								
Controller (Optional)		Remote controller								
Connecting pipe	Gas side	mm	22.2		28.6		22.2		28.6	
	Liquid side	mm	12.7		15.9		12.7		15.9	
	Drain port (nominal dia)	mm	25 (Both sides of male screw)							


Drawings

Unit : mm


MMF-AP0725DHP-VA/VB,
MMF-AP0965DHP-VA/VB




MMF-AP1445DHP-VA/VB,
MMF-AP1925DHP-VA/VB



MMF-AP0725HP-VA/VB,
MMF-AP0965HP-VA/VB



MMF-AP1445HP-VA/VB,
MMF-AP1925HP-VA/VB




LARGE CAPACITY FLOOR STANDING


Sound pressure levels

Unit : dB(A)


MMF-AP0725DHP-VA/VB




MMF-AP0965DHP-VA/VB




MMF-AP1445DHP-VA/VB




MMF-AP1925DHP-VA/VB




MMF-AP0725HP-VA/VB




MMF-AP0965HP-VA/VB



MMF-AP1445HP-VA/VB




MMF-AP1925HP-VA/VB




Air diffusion

Unit : m/s


MMF-AP0725HP-VA(VB)




MMF-AP0965HP-VA(VB)



MMF-AP1445HP-VA(VB)



MMF-AP1925HP-VA(VB)



Large capacity floor standing connectors

∴ Available

CN32	CN60	CN61	CN70	CN73	CN80
Additional ventilation control from remote control	Operation status signal output (Cooling, fan, thermo-on)	External On/Off, operation output and alarm output	Warning symbol on remote control based on signal input.	Forced IDU thermo-off based on signal input	Forced IDU thermo-off and IDU lock based on signal input
•	TCB-PCUC2E pcb needed	•	TCB-PCUC2E pcb needed	TCB-PCUC2E pcb needed	TCB-PCUC2E pcb needed

Large capacity floor standing duct type

MMF-AP0**4DH-V

MMF-AP1**4DH-V

Floor standing <duct type>



(50 Hz/60 Hz)

MMF-AP0724DH-V/MMF-AP0964DH-V

MMF-AP1444DH-V/MMF-AP1924DH-V

MMF-AP0724DH-V, MMF-AP0964DH-V

MMF-AP1444DH-V, MMF-AP1924DH-V



(Unit: mm)

Technical specifications

Model name	MMF-	AP0724DH-V	AP0964DH-V	AP1444DH-V	AP1924DH-V	
Cooling capacity*1	(kW/Btu/h)	22.4 / 78,500	28.0 / 98,300	45.0 / 153,600	56.0 / 191,100	
Electrical characteristics	Power requirements	3 phase 50/60Hz 400V(Separate power supply for indoor units is required.)				
	Power consumption 50 Hz/60 Hz	(kW)	0.59/0.70	0.80/0.99	1.04/1.28	1.79/2.26
External dimensions	Height	(mm)	1820		1870	
	Width	(mm)	890		1300	
	Depth	(mm)	540		760	
Total weight	(kg)	170	170	280	290	
Fan unit*2	Standard air flow	(m ³ /h)	3600	4200	7200	8400
	Motor output	(kW)	1.5	1.5	22	3.7
	External static pressure (50Hz/60Hz)	(Pa)	43/122	39/148	28/111	86/222
	Gas side	(mm)	ø22.2		ø28.6	
Connecting pipe	Liquid side	(mm)	ø12.7		ø15.9	
	Drain port	(nominal dia.)	25 (Both sides of male screw)			
Sound pressure level*3	(dB(A))	54/56	55/57	61/63	62/64	

Note 1 : The capacities and electrical characteristics are measured under the conditions specified by JIS B 8615.

Note 2 : As air volume is fixed, by remote controller, air volume cannot be changed.

When required high static pressure and air volume change, a pulley change is requested.

Note 3 : The sound level are measured in an anechoic chamber in accordance with JIS B 8616.

Normally, the sound level measured in the actual operating environment become bigger than the rated figures due to the effects of external sound.

Note : Rated conditions : Cooling : Indoor air temperature 27°C DB/19°C WB, Outdoor air temperature 35°C DB

Large capacity floor standing direct type

MMF-AP0**4H-VA/VB

MMF-AP1**4H-VA/VB

Floor standing <direct type>

(50 Hz)



MMF-AP0724H-VA/MMF-AP0964H-VA
MMF-AP1444H-VA/MMF-AP1924H-VA

(60 Hz)

MMF-AP0724H-VB/MMF-AP0964H-VB
MMF-AP1444H-VB/MMF-AP1924H-VB

MMF-AP0724H-VA/VB, MMF-AP0964H-VA/VB

MMF-AP1444H-VA/VB, MMF-AP1924H-VA/VB



(Unit: mm)

Technical specifications

Model name (50Hz/60Hz)	MMF-	AP0724H-VA/VB	AP0964H-VA/VB	AP1444H-VA/VB	AP1924H-VA/VB	
Cooling capacity*1	(kW/Btu/h)	22.4 / 78,500	28.0 / 98,300	45.0 / 153,600	56.0 / 191,000	
Electrical characteristics	Power requirements	3 phase 50/60Hz 400V (Separate power supply for indoor units is required.)				
	Power consumption 50 Hz/60 Hz	(kW)	0.56/0.53	0.80/0.79	1.24/1.19	2.07/2.05
External dimensions	Height	(mm)	2,130		2,280	
	Width	(mm)	890		1,300	
	Depth	(mm)	540		760	
Total weight	(kg)	182	188	320	320	
Fan unit*2	Standard air flow	(m ³ /h)	3,600	4,200	7,200	8,400
	Motor output	(kW)	0.75	1.5	22	2.2
Connecting pipe	Gas side	(mm)	ø22.2		ø28.6	
	Liquid side	(mm)	ø12.7		ø15.9	
	Drain port	(nominal dia.)	25 (Both sides of male screw)			
Sound pressure level*3	(dB(A))	62	63	64	66	

Note 1: The capacities and electrical characteristics are measured under the conditions specified by JIS B 8615.

Note 2: As air volume is fixed, by remote controller, air volume cannot be changed.

When required high static pressure and air volume change, a pulley change is requested.

Note 3: The sound level are measured in an anechoic chamber in accordance with JIS B 8616.

Normally, the sound level measured in the actual operating environment become bigger than the rated figures due to the effects of external sound.

Note: Rated conditions Cooling: Indoor air temperature 27°C DB/19°C WB, Outdoor air temperature 35°C DB




Key features

The Dx-coil interface enables the connection between third party AHU and TOSHIBA SMMS-7 with maximum capacity of the connectable AHU up to 60 HP for multiple Dx-coil (TA Control Type) interface and 20 HP for single Dx-coil (DDC) interface.

Technical specifications

Dx-coil interface type		Dx-valve kit					Dx-coil interface type		Dx-coil controller	
		RBM-A101VAE		RBM-A201VAE					TA Control Type	DDC Control Type
Model Name		RBM-A101VAE		RBM-A201VAE			Model Name		TCB-IFDTA201E	TCB-IFDDC201E
HP		8	10	16	18	20	Power Supply		1ph 50Hz 220V - 240V / 1ph 60 Hz 220V	
Dimension	Height (mm)	420					Dimension	Height (mm)	420	
	Width (mm)	420						Width (mm)	330	
	Depth (mm)	420						Depth (mm)	95	
Weight (kg)		3.0					Weight (kg)		3.5	4.5




Combination

Type of DX-COIL	TA Control Type						DDC Control Type		
	Dx-coil controller	Normal		Interlaced, Split face			Normal		
		Dx-valve kit	Dx-coil controller	Dx-valve kit		Dx-coil controller	Dx-valve kit		
Model Name	TCB-IFDTA201E	RBM-A101VAE	RBM-A201VAE	TCB-IFDTA201E	RBM-A101VAE	RBM-A201VAE	TCB-IFDDC201E	RBM-A101VAE	RBM-A201VAE
Connectable AHU Capacity	8 HP	1	1	-	-	-	1	1	-
	10 HP	1	1	-	-	-	1	1	-
	16 HP	1	-	1	2	2	-	1	1
	18 HP	1	-	1	2	2	-	1	1
	20 HP	1	-	1	2	2	-	1	1
	32 HP	1	-	2	2	-	2	-	-
	36 HP	1	-	2	2	-	2	-	-
	40 HP	1	-	2	2	-	2	-	-
	48 HP	-	-	-	3	-	3	-	-
	54 HP	-	-	-	3	-	3	-	-
	60 HP	-	-	-	3	-	3	-	-


Operation Pattern 1: TA Control

DX-coil controller is controlled by TA Sensor.



Operation Pattern 2: DDC Control

DX-coil controller is controlled by DDC Direction



*1 = Direct Digital Controller (Local Supply)

*2 = Temperature of Fresh air must be within the Guideline

For more detail, please contact your local sales company.

Fresh air intake indoor unit type

MMD-AP*HFE**




Air controller for fresh-air intake

Fresh-air intake often influences the system, rendering normal control of the air conditioner difficult, or placing large loads on the system and its cooling performance.

Therefore it is frequently adopted to handle the fresh air to a certain condition before the fresh air will enter in the main air conditioner.

This device is known as a fresh air intake indoor unit.

For some application need to get all fresh air intake connect to VRF system, SMMS-7 are available connected to 1-3 Fresh air Units up to 24 HP



NOTE: The fresh air intake indoor unit is an air conditioner provided to handle the fresh air load and is not to control the room temperature. For correspondence to the load of the indoor air controller, set an air conditioner separately.

Technical specifications

Model name		MMD-	AP0481HFE	AP0721HFE	AP0961HFE
Cooling capacity*1		(kW/Btu/h)	14.0 / 47,800	22.4 / 78,500	28.0 / 98,300
Electrical characteristics	Power requirement	(kW)	1-phase 50Hz 230V (220-240V) / 1-phase 60Hz 220V (208V-230V) (Separate power supply for indoor units required.)		
	Power consumption 50Hz/60Hz	(kW)	0.28/0.34	0.45/0.5	0.52/0.65
External dimensions	Main unit	Height	(mm)	492	
		Width	(mm)	892	1,392
		Depth	(mm)	1,262	
Total weight		(kg)	93	144	
Fan unit	Standard air flow	(m ³ /h)	1,080	1,680	2,100
	Motor output	(kW)	0.160	0.160x2	
	External static pressure 50 Hz/60 Hz	(Pa)	170-210-230 / 115-215-260	140-165-180 / 150-210-235	160-190-205 / 80-180-220
	Air flow limit Lower limit/Upper limit	(m ³ /h)	756/1,188	1,176/1,848	1,470/2,310
Connecting pipe	Gas side	(mm)	ø15.9		
	Liquid side	(mm)	ø9.5		
	Drain port	(mm)	25		
Sound pressure level*2 (High/Med./Low)		(dB(A))	45/43/41		46/45/44
Operation range	Cooling*3	(°C)	5 - 43		

* The setting temperature is 16 - 27°C (standard FCU...18 - 29°C).
 * An optional humidifier is not available with fresh air intake indoor unit.
 * Height difference between fresh air intake indoor units must be within 0.5 m. Height difference between fresh air intake indoor unit and standard FCU must be within 30 m.

NOTE 1 Rated conditions Cooling: Outdoor air temperature 33°C DB/28°C WB setting temperature 18°C
 Heating: Outdoor air temperature 0°C DB/-2.9°C WB setting temperature 25°C
 Piping: Length 7.5 m / Height 0 m
NOTE 2 Normally, the values measured in the actual operating environment become large than the indicated values due to the effects of external sound.
NOTE 3 * When supply air temperature is "setting temperature + 3°C" or less, fresh air intake indoor unit operates as FAN mode.
 * When supply air temperature is 19°C or less, Fresh Air Intake Indoor unit operates as FAN mode.

Use conditions

- In COOL mode, if temperature of the fresh air is below the setup temp. of +3°C, FAN status is automatically made. When temperature of the fresh air is below 19°C, FAN status is also made regardless of the setup temperature.




Operable mode and discharge temperature setup range

Operation mode	At shipment from factory	Setup range
COOL	18°C	16 to 27°C





MMD-AP0481HFE to AP0961HFE

Long hole for M10 hanging bolt

Type	Hole dia.-Width x Length
0481	4-φ12 x 40
0721, 0961	4-φ12 x 92




Space required for installation and servicing



Model MMD-	A	B	C	D	E	F	G	H	I	J	K	L	M	N
AP0961HFE	1392	1260	250	250	250	250	250	250	250	250	10-M6	10-M6	φ22.2 brazin g	φ12.7 flare
AP0721HFE	1392	1260	250	250	250	250	250	250	250	250	10-M6	10-M6	φ22.2 brazin g	φ12.7 flare
AP0481HFE	892	810	215	107.5	107.5	215	—	250	250	—	8-M6	6-M6	φ15.9 flare	φ9.5 flare

(Unit: mm)

Options



Air-to-Air heat exchanger with DX-coil

MMD-VN***HEX1E/HEX1E2



◀ Greater comfort and reduce load

Functionality built into the cooling system reduces load on cooling beyond that of the heat exchanger itself. This improves air quality and ensures maximum comfort throughout room being cooled.

◀ Flexible control

Supply and exhaust fan speed ratios can be changed for improved air volume control that best matches the needs of the environment and location.

◀ Free cooling at night

When the air outdoors is cooler at night, the system expels warm air from the room. This reduces the air conditioning load the next day for improved energy efficiency.




Remote controller
NRC-01HE

Technical specifications				MMD-	VN502HEX1E	VN802HEX1E	VN1002HEX1E2
Model name				MMD-	VN502HEX1E	VN802HEX1E	VN1002HEX1E2
Fresh air conditioning load	Cooling (*1)	(kW/Btu/h)			4.10 (1.30) / 14,000	6.56 (2.06) / 22,500	8.25 (2.32) / 28,200
	Heating (*1)	(kW)			5.53 (2.33)	8.61 (3.61)	10.92 (4.32)
Power supply					1-phase 50Hz 230V (220-240V) / 1-phase 60Hz 220V		1-phase 60Hz 220V
					(Separate power supply for indoor units required.)		
Temperature exchange efficiency 50Hz / 60Hz	High	(%)			70.5/70.5	70.0/70.0	65.5
	Mid	(%)			70.5/70.5	70.0/70.0	65.5
	Low	(%)			71.5/72.0	72.5/73.0	68.0
Enthalpy exchange efficiency 50Hz / 60Hz	Cooling	High	(%)		56.5/56.5	56.0/56.0	52.0
		Mid	(%)		56.5/56.5	56.0/56.0	52.0
		Low	(%)		57.5/58.0	59.0/59.5	55.0
	Heating	High	(%)		68.5/68.5	70.0/70.0	66.0
		Mid	(%)		68.5/68.5	70.0/70.0	66.0
		Low	(%)		69.0/69.0	73.0/73.5	69.0
Fan unit 50Hz / 60Hz	Standard air flow	High	(m ³ /h)		500/500	800/800	950
		Mid	(m ³ /h)		500/500	800/800	950
		Low	(m ³ /h)		440/410	640/600	800
	External static pressure	High	(Pa)		120/200	120/190	195
		Mid	(Pa)		105/170	100/155	160
		Low	(Pa)		115/150	105/130	130
Sound pressure 50Hz / 60Hz	High	(dB(A))		37.5/40.0	41.0/43.0	43.5	
	Mid	(dB(A))		36.5/38.0	40.0/42.0	42.0	
	Low	(dB(A))		34.5/36.5	38.0/37.0	40.0	
External dimensions	Height	(mm)		430	430	430	
	Width	(mm)		1140	1189	1189	
	Depth	(mm)		1690	1739	1739	
Total weight		(kg)		84	100	103	
Connecting piping	Gas side	(mm)		ø9.5		ø12.7	
	Liquid side	(mm)			ø6.4		
Drain port (Nominal dia.)		(mm)			25(Polyvinyl chloride tube)		


(*1) Cooling and heating capacities are based on the following conditions:
 Cooling capacities are based on : indoor temperature :27 °C DB/19°C WB, Outdoor temperature : 35°C DB
 Heating capacities are based on : indoor temperature :20 °C DB, Outdoor temperature : 7 °C DB/6°C WB
 Fan is based on High and Middle
 (): The figures in () indicate the heat reclaimed from the heat recovery ventilator.

*If high humidity air (about 80% or more of relative humidity), such as fog, is inhaled by the Heat Exchanger, dew condensation water may trickle from a main body.


MMD-VN502HEX1E



MMD-VN802HEX1E to VN1002HEX1E/2



Options



Air-to-Air heat exchanger (Stand alone unit)

VN-M***HE



- ◀ **Greater comfort and reduced load**
Easily integrated into air conditioning systems of 150 m³/h to 2000 m³/h air volume, the air-to-air heat exchangers use exhaust air to pre-condition the incoming air, thus reducing the cooling or heating load and the overall size of the required system.
- ◀ **Flexible control**
Supply and exhaust fan speed ratios can be changed for improved air volume control that best matches the needs of the environment and location.

- ◀ **Free cooling at night**
When the air outdoor is cooler at night, the system expels warm air from the room. This reduces the air conditioning load the next day for improved energy efficiency.
- ◀ **Easy maintenance**
The heat exchange element can be washed in water.



Remote controller NRC-01HE

* Do not connect to refrigerant piping from outdoor unit. Control wires can be connected.


Technical specifications

Model name	VN-	M150HE	M250HE	M350HE	M500HE	M650HE	M800HE	M1000HE	M1500HE	M2000HE	
Power supply (V)	1-phase 50Hz 230V (220-240V) / 1-phase 60Hz 220V (Separate power supply for indoor units required.)										
Power consumption 50Hz/60Hz (W)	(Extra high)	68-78/76	123-138/131	165-182/209	214-238/260	262-290/307	360-383/446	532-569/622	751-786/928	1084-1154/1294	
	High	59-67/65	99-111/105	135-145/162	176-192/206	240-258/283	339-353/408	494-538/589	708-784/830	1032-1080/1220	
	Low	42-47/45	52-59/54	82-88/94	128-142/144	178-191/206	286-300/333	353-370/411	570-607/660	702-742/818	
Air volume (m ³ /h)	(Extra high)	150/150	250/250	350/350	500/500	650/650	800/800	1000/1000	1500/1500	2000/2000	
	High	150/150	250/250	350/350	500/500	650/650	800/800	1000/1000	1500/1500	2000/2000	
	Low	110/110	155/155	210/210	390/390	520/520	700/700	755/755	1200/1200	1400/1400	
External static pressure (Pa)	(Extra high)	82-102/99	80-98/97	114-125/167	134-150/181	91-107/134	142-158/171	130-150/185	135-156/165	124-143/165	
	High	52-78/59	34-65/38	56-83/33	69-99/63	58-82/68	102-132/102	97-122/120	103-129/108	92-116/102	
	Low	47-64/46	28-40/22	65-94/39	62-92/44	61-96/52	76-112/58	84-127/55	112-142/109	110-143/87	
Sound pressure level (dB(A))	(Extra high)	26-28/27.5	29.5-30/31.5	34-35/35.5	32.5-34/33.5	34-36/35.5	37-38.5/38	39.5-40.5/41.5	38-39/39.5	41-42.5/42.5	
	High	24-25.5/24.5	25-27/25	30-32/29.5	29.5-31/29	33-34/34	35.5-37/35	38.5-40/39	36.5-37.5/36.5	39.5-41/40	
	Low	20-22/20	21-22/21	27-29/23.5	26-29/24.5	31-32.5/29.5	33.5-35/32.5	34-35.5/33.5	36-37.5/35.5	37-38/36.5	
Temperature exchange efficiency (%)	(Extra high)	81.5/81.5	78/78	74.5/74.5	76.5/76.5	75/75	76.5/76.5	73.5/73.5	76.5/76.5	73.5/73.5	
	High	81.5/81.5	78/78	74.5/74.5	76.5/76.5	75/75	76.5/76.5	73.5/73.5	76.5/76.5	73.5/73.5	
	Low	83/83	81.5/81.5	79.5/79.5	78/78	76.5/76.5	77.5/77.5	77/77	79/79	77.5/77.5	
Enthalpy exchange efficiency (%)	for cooling	(Extra high)	69.5/69.5	65/65	60.5/60.5	64.5/64.5	61.5/61.5	64/64	60.5/60.5	64/64	60.5/60.5
		High	69.5/69.5	65/65	60.5/60.5	64.5/64.5	61.5/61.5	64/64	60.5/60.5	64/64	60.5/60.5
		Low	71/71	69/69	67/67	66.5/66.5	64/64	65.5/65.5	64.5/64.5	67/67	65.5/65.5
Dimensions (Length x Width x Height) (mm)		900 x 900 x 290			1140 x 1140 x 350		1189 x 1189 x 400		1189 x 1189 x 810		
Weight (kg)		36		38		53		70		143	
Duct diameter (mm)		100		150		200		250		inside: 250, outside: 283 x 730	
Operating range	Around unit	-10°C – 40°C 80% RH or less									
	Outdoor Air (OA)	-15°C (*1) – 43°C RH									
	Return Air (RA)	5°C – 40°C 0% RH or less									

* Air volume can be changed over to high (extra high) mode or low mode.
 * Sound pressure level is measured 1.5m below the center of the unit.
 * Sound pressure level is the value which was measured at the acoustic room.
 * The actual values in an external operating environment are generally higher than the indicated values due to the contribution from ambient noise.
 * Sound pressure level is less than 70 dBA


*If high humidity air (about 80% or more of relative humidity), such as fog, is inhaled by the Heat Exchanger, dew condensation water may trickle from a main body.

VN-M150HE to VN-M350HE




(Unit: mm)

VN-M500HE, VN-M650HE




(Unit: mm)

VN-M800HE, VN-M1000HE



(Unit: mm)

VN-M1500HE, VN-M2000HE



(Unit: mm)

Indoor unit accessories


Indoor unit	Parts Name	Model Name	Applied Model	Notes	Remarks
4-way air discharge cassette type	Ceiling panel	RBC-U31PG(W)-E	MMU-AP***4HP1-E	Required accessory	
	Fresh air inlet box	TCB-GB1602UE		For fresh air intake by using the knockout hole of fresh air filter chamber. (dia.=100 mm)	Use with TCB-GFC1602UE
	Fresh air filter chamber	TCB-GFC1602UE		For fresh air inlet box	
	Auxiliary fresh air flange	TCB-FF101URE2		For easy fresh air intake by using the knockout hole of indoor unit. (dia.=100 mm)	
	Spacer for height	TCB-SP1602UE		Height=50 mm	
	Air discharge direction kit	TCB-BC1602UE		Air direction charge by cutting off air discharge port (3 pcs.)	
Compact 4-way cassette type	Ceiling panel	RBC-UM21PG(W)-E	MMU-AP***7MH-E	Required accessory	
	Auxiliary fresh air flange	TCB-FF101URE2		For easy fresh air intake by using the knockout hole of indoor unit. (dia.=100 mm)	
	Occupancy sensor	TCB-SIR41UM-E			
2-way air discharge cassette type	Ceiling panel	RBC-UW283PG(W)-E RBC-UW803PG(W)-E RBC-UW1403PG(W)-E	MMU-AP0072 to 0152WH1 MMU-AP0182 to 0302WH1 MMU-AP0362/0482/0562WH1	Required accessory	
	Super long life filter	TCB-LF283UW-E	MMU-AP0072 to 0152WH1	Dust collecting effect: 50% (Weight method)	Use with TCB-FC283UW-E
		TCB-LF803UW-E	MMU-AP0182 to 0302WH1		Use with TCB-FC803UW-E
		TCB-LF1403UW-E	MMU-AP0362/0482/0562WH1		Use with TCB-FC1403UW-E
	Filter chamber	TCB-FC283UW-E	MMU-AP0072 to 0152WH1	For super long life filter	
		TCB-FC803UW-E	MMU-AP0182 to 0302WH1		
	Auxiliary fresh air flange	TCB-FC1403UW-E	MMU-AP0362/0482/0562WH1		
1-way air discharge cassette type	Ceiling panel	RBC-UY136PG RBC-US21PGE	MMU-AP***2WH1 MMU-AP***4YH1-E	Required accessory	
	Front air discharge unit	TCB-BUS21HWE	MMU-AP***4SH1-E	Required accessory	
	Auxiliary fresh air flange	TCB-FF101URE2		For easy fresh air intake by using the knockout hole of indoor unit. (dia.=100 mm)	
Slim duct type	Auxiliary fresh air flange	TCB-FF101URE2	MMD-AP***4SPH1-E	For fresh air intake by using the knockout hole of indoor unit. (dia.=100	
Concealed duct type	Spigot shaped flange	TCB-SF56C6BPE	MMD-AP0076 to 0186BHP1-E		
		TCB-SF80C6BPE	MMD-AP0246/0276/0306BHP1-E		
		TCB-SF160C6BPE	MMD-AP0366/0486/0566BHP1-E		
Concealed duct high static pressure type	Long Life Filter Kit	TCB-LK801D-E	MMD-AP0186/0246/0276HP1-E		
		TCB-LK1401D-E	MMD-AP0366/0486/0586HP1-E		
	Auxiliary fresh air flange	TCB-FF151US-E	MMD-AP***6HP1-E		
	Long life filter kit	TCB-LK2801DP-E	MMD-AP0726/0966HP-E	Flange shaped, Mount chassis directly, Upside down mountable	
Drain pump kit	TCB-DP40DPE	MMD-AP0726/0966HP-E	Lift up 500 mm		
Ceiling type	Drain pump kit	TCB-DP31CE	MMC-AP0158/0188HP-E MMC-AP0248 to 0568HP-E	Stand-up 600 or less (from bottom face of ceiling)	Use with TCB-KP13CE Use with TCB-KP23CE
	Elbow piping kit	TCB-KP13CE TCB-KP23CE	MMC-AP0158/0188HP-E MMC-AP0248 to 0568HP-E	Needed when drain pump kit is used	
	Drain pump kit	TCB-DP31HEXE	MMD-VN502 to 1002HEX1E	Stand-up 330 mm or less (from bottom face of ceiling)	
Fresh air intake indoor unit type	High-efficiency filter 65	TCB-UFM3DE	MMD-AP0721/0961HFE	Dust collecting effect: 65% (NBS Colorimetric method)	Use with TCB-PF3DE
		TCB-UFM4D-1E	MMD-AP0481HFE		Use with TCB-PF4D-1E
	High-efficiency filter 90	TCB-UFH7DE	MMD-AP0721/0961HFE	Dust collecting effect: 90% (NBS Colorimetric method)	Use with TCB-PF3DE
		TCB-UFH8D-1E	MMD-AP0481HFE		Use with TCB-PF4D-1E
	Long life prefilter	TCB-PF3DE	MMD-AP0721/0961HFE	Dust collecting effect: 50% (Weight method)	
		TCB-PF4D-1E	MMD-AP0481HFE		
Filter chamber	TCB-FCY51DFE	MMD-AP0481HFE	For high-efficiency filter or long life prefilter		
Drain pump kit	TCB-FCY100DE	MMD-AP0721/0961HFE	Stand-up 330 or less (from bottom face of ceiling)		

		Combination Pattern					
1) Accessory for 4-way air discharge cassette type: combination pattern		1	2	3	4	5	6
		Ceiling panel	Fresh air inlet box + Fresh air filter chamber	Fresh air filter chamber	Auxiliary fresh air flange	Space for height adjustment	Air discharge direction kit
1	Ceiling panel		OK	OK	OK	OK	OK
2	Fresh air inlet box + Fresh air filter chamber	OK			OK	—	OK
3	Fresh air filter chamber	OK			OK	OK	OK
4	Auxiliary fresh airflange	OK	OK	OK		OK	OK
5	Spacer for height adjustment	OK	—	OK	OK		OK
6	Air discharge direction kit	OK	OK	OK	OK	OK	




Remote controllers

Air-conditioning Management System on site



1. LonWorks® : Registered trademark by Echelon corporation.
 2. BACnet® : ANSI/ASHRAE 135-1995, A data Communication Protocol for Building Automation and Control Network.
 3. Modbus® : Registered trademark by Schneider E.



Wire remote controller/Wireless remote controller

<p>Wired remote Controller RBC-AMS55E-ES RBC-AMS55E-EN</p>	<p>Wired remote controller with Weekly timer RBC-AMS41E</p>	<p>Wired remote controller RBC-AMT32E</p>	<p>Simple remote controller RBC-AS41E</p>	<p>Wireless remote controller</p>	<p>Remote Sensor TCB-TC411E</p>

Wired remote controller



NEW features

**Wired remote controller
RBC-AMS55E-EN
RBC-AMS55E-ES**

Wired remote controller with a **summer time shift**-featuring LCD with **AM/PM display**.

- 7-day timer function.
- Multi-language available.
- Possibility to set and display the room name to easily set-up and monitor the working parameter.
- New modern and desirable controller design with menu driven display.
- Save mode by schedule timer to optimise energy consumption.
- Room temperature display always available.
- Two "Hot Keys" (F1, F2) for easy operation of air conditioner functions.
- Easy to read layout including display of indoor unit model name and serial number.
- Built-in backup power. Settings are kept in memory up to 72 hours in case of power failure.
- Remote TA sensor available in controller.
- Can be connected to a single indoor unit or a group of up to 8 indoor units.



**Standard Remote controller
RBC-AMT32E**

Standard wired remote controller can be connected to a single indoor unit or a group of up to 8 indoor units.

Power save operation limits the greatest current value. The remote controller allows error to be displayed while the protective device works or a error occurs.



**Remote controller with weekly timer (7-day timer function)
RBC-AMS41E**

- Clock display
- Schedule timer: Possible to program schedule timer (7-day timer) function
- Possible to program 8 functions for each day of the week

*The following items can be set in program: operation time, operation start/stop, operation mode, temperature setting, restriction on button operation



**Simple wired remote controller
RBC-AS41E**

- Start/Stop
- Temperature setting
- Air flow changing
- Check code display

Wireless remote controller



Wireless remote controller kit & sensor unit (receiver unit)

- Start/Stop •Changing mode •Temperature setting
- Air flow changing
- Timer function
Either "ON" time or "OFF" time or "CYCLIC" can be set how many 30 min. later ON or OFF is operated.
- Control by 2 remote controllers is available. Two wireless remote controllers can operate one indoor unit. The indoor unit can then be operated separately from the two different locations.
- Check code display

*The wireless remote control cannot be connected to concealed duct high static pressure type.




RBC-AX33CE
Integral receiver
(For ceiling) (MMC-AP***HP-E)
(MMU-AP***4SH1-E)



TCB-AX32E
Stand alone receiver
(For 4-way air discharge cassette, compact 4-way cassette
2-way air discharge cassette, ceiling, concealed duct standard, slim duct, floor standing cabinet, floor standing, 1-way discharge cassette (MMU-AP ***4YH1/SH1-E)



RBC-AX32U(W)-E
Integral receiver (For 4-way air discharge cassette)
(MMU-AP***4HP1-E)



RBC-AX23UW(W)-E
Integral receiver (For 2-way air discharge cassette)
(MMU-AP***2WH1)



RBC-AX32UM(W)-E
Integral receiver
(MMU-AP***7MH-E)
(For compact 4-way discharge cassette)

Central remote controller



Central remote controller
BMS-CM1280TLE

- **Operation**
Individual operation of 128 indoor units available
Return Back Operation
Weekly Schedule Operation* (ON/OFF)
* Schedule timer necessary
- **Monitoring**
Zone setting (64 zones x 2)
Individual unit operation mode operation restriction
Alarm display
Control input
Status output



ON-OFF controller
TCB-CC163TLE2

- Individual control of up to 16 indoor units.
- Setting of simultaneous ON/OFF 3 times per day combined with the weekly timer.



Schedule timer
TCB-EXS21TLE

- **Schedule timer mode**
 - 6 programmings per day
 - Enabling 8 groups to be programmed
 - A maximum of 64 indoor units can be controlled
 - A maximum of 100 hours back-up power supply
- **Weekly timer mode**
 - 7 types of weekly schedule and 3 programmings per day

Other



Remote sensor
TCB-TC41LE

Install this sensor when outside air has been introduced or when overcooling are being minimised.




Wired remote controller for air to air heat exchanger
NRC-01HE

- Up to 8 units of the Air to Air Heat Exchanger can be operated using this remote controller.
- Control by 2 remote controllers is available.
Two remote controllers can operate a single Air to Air Heat Exchanger.
- Air conditioning units may be controlled in addition to controlling the Air to Air Heat Exchanger.
- Central control allows linked ON/OFF operation of air conditioner and Air to Air Heat Exchanger.
- Central control can be set to allow standalone operation of the Air to Air Heat Exchanger.
- Switchable ventilation modes (Automatic/Air to Air/Normal)
- Switchable ventilation air volume (Extra-high/High-Low)

Building management systems


SMART BMS MANAGER / SMART BMS MANAGER WITH DATA ANALYSER



Touch screen controller

TOUCH SCREEN CONTROLLER

BMS-CT5121E





SMART BMS MANAGER
BMS-SM1280HTLE


SMART MANAGER WITH DATA ANALYSER
BMS-SM1281ETLE



Web browser control software

- List View available - Displays all indoor units in one screen
- Set View available - Shows basic indoor unit settings on main screen
- Advanced operation and master schedule functions available
- Advanced operation & master schedules can be set on a calendar
- Up to 4 concurrent users can be connected
- Up to 32 user accounts can be programmed with different levels of access (at least 1 must be administrator level)
- Energy monitoring and billing functions are available. Power meter locally supplied energy.
- Additional digital I/O device is available
- Thin profile controller and separate power supply unit enables easy installation
- Maximum 128 FCU

Energy monitoring display



3D energy view



Daily energy view



TOUCH SCREEN CONTROLLER
BMS-CT5121E

• Touch screen controller

Using the touch screen controller provides a clear display and enables easy operation.


A maximum of 512 units / groups are controllable.

• Energy monitoring and billing application


Power meter locally supplied Energy

• Web connection

• Layout diagram function (Option)



LAYOUT DIAGRAM FUNCTION (OPTION)



GRAPH FUNCTION

FEATURES

- Icon display
- Return back function
- Save & demand control for outdoor unit
- Ventilation unit control & monitoring
- Setting temp. range control
- Setting temp. shift
- Layout diagram function (Option)



Relay Interface BMS-IFWH5E
For Energy Monitoring to connect power meter

Relay Interface BMS-IFDD03E
to connect external digital input/output




Relay Interface BMS-IFLSV4E
For TCS-NET (Max. 64 FCU/Unit)

Open network systems


BACnet® system



LonWorks®



Modbus®





BN Interface
BMS-IFBN640TLE

• **BACnet®**

The BACnet® system operates in conjunction with the BACnet®. Server uses object signals to provide the following functions:

• **Control**

- ON/OFF
- Temperature setting
- Fan speed
- Max 64 FCU

• **Monitoring**

- ON/OFF
- Operation mode
- Temperature setting
- Room temperature
- Local remote controller : permit / prohibit



LN Interface
TCB-IFLN642TLE

• **LonWorks® LN Interface**

The LonWorks® interface manages the SMMS-e air conditioning system as a Lon device to communicate with the customer's Building Management System and to monitor operational status.

A maximum of 64 units / groups are controllable per interface.

• **SNVT signal**

Signals and provides the following functions:

• **Control**

- ON/OFF
- Temperature setting
- Fan speed
- Max 64 FCU

• **Monitoring**

- ON/OFF
- Operation mode
- Temperature setting
- Room temperature
- Local remote controller : permit / prohibit



Modbus® Interface
TCB-IFMB641TLE

• **Modbus®**

The Modbus® interface manages the SMMS-e air conditioning system as a Modbus® device to communicate with the customer's Building Management System.

Accessible to 64 units / groups per one TCB-IFMB641TLE, 15 TCB-IFMB641TLEs on one Modbus® Master (prepared by user).

Signals and provides the following functions:

• **Control**

- ON/OFF
- Temperature setting
- Fan speed
- Max 64 FCU

• **Monitoring**

- ON/OFF
- Operation mode
- Temperature setting
- Room temperature
- Local remote controller : permit / prohibit

1. LonWorks®: Registered trademark Echelon corporation.

2. BACnet®: ANSI/ASHRAE 135-2008, A data Communication Protocol for Building Automation and Control Networks.

3. Modbus® is a registered trademark of Schneider E.

Application controls

TCB-PCDM4E



Size: 71 × 85 (mm)

Power peak-cut control

• Feature

The upper limit capacity of the outdoor unit is restricted based on the outdoor power peak selected setting.

• Function

Two control settings are selectable by setting SW07 on the interface P.C. board on the outdoor unit.

TCB-PCMO4E



Size: 55.5 × 60 (mm)

Snowfall fan control

• Feature

The upper limit capacity of the outdoor unit is restricted based on the outdoor power peak selected setting.

External master ON/OFF control

• Feature

The outdoor unit starts or stops the system.

Night operation (Sound reduction) control

• Feature

Sound level can be reduced by restricting the compressor and fan speeds.

Operation mode selection control

• Feature

This control can restrict the selectable operation modes.

TCB-PCIN4E



Size: 73 × 79 (mm)

Error/Operation output control

• Feature

Enables external output of error and operation signals.

Compressor operation output

• Feature

Enables external signal output for each compressor that is in operation within any given outdoor unit. This feature provides a practical method for calculating total operating times for each compressor.

Operating rate output

• Feature

External output of system operating rates enables remote monitoring of operating conditions.

TCB-IFCB-4E2




Size: 200 × 170 × 66 (mm)

Remote location ON/OFF control box

• Feature

Start and stop of the air conditioner is possible by an external signal and indication of operation/ alarm externally.




Monitoring


ON/OFF status (for indoor unit)
 Alarm status (system & indoor unit stop)
 ON/OFF command
 Air conditioner can be turned ON/OFF by the external signals.
 The external ON/OFF signals will initiate the signals shown below.

BMS-CT1280E


**TOUCH SCREEN CONTROLLER
 BMS-CT1280E**



BMS-IWF0320E



General Purpose Interface



Concept

- Controls the operation status of each indoor unit.
- ON/OFF control of peripheral equipment via the relay point of Toshiba's BMS. (1 pt only)


Standard function

Central remote controller and Building Management System devices can control ON/OFF function via digital I/O ports.

Optional function

Control using the following channels: 4-channel relay control, 6-channel digital input, 2-channel analog voltage input and output, and 2-channel temperature measurement functions via Modbus® I/F.

Analog Interface



Concept

- Provides access to 64 indoor units.
- Does not require special network knowledge.
- Can control each indoor unit on TCC-LINK, (on/off, temperature setting, airflow volume, louver position), and monitor status based on 0-10V DC voltage input.
- Enables relay control and status monitoring of general-purpose I/F TCB-IFCG1TLE.

Installation and the use of refrigerants not specified by Toshiba Carrier Corporation

Toshiba refrigeration and air-conditioning units are designed and manufactured on the assumption that the product is used with a specific refrigerant suitable for each unit.

We have recently seen some cases where the type of refrigerant used is different from the one originally installed in the product. Such actions may cause mechanical defects, malfunctions, failures and in some cases result in a serious safety issue. Therefore do not install any refrigerant other than the one specified by Toshiba Carrier Corporation for its respective products.

The type of the refrigerant used for each of our products is shown in the accompanying owners manual, or on the product label attached on the product itself.

Toshiba Carrier Corporation shall not assume any liability for failures, malfunctions or safety in its products if the refrigerant used is different from the one specified.

SAFETY PRECAUTIONS

For operation:

- Before use, read through the operating instructions to ensure proper use.

Concerning the purpose for which the air conditioners are to be used

- The air conditioners presented in this catalogue are air conditioning/heating units to be used solely by general consumers.
 - Do not use these air conditioners for special applications such as for the storage of food items, animals, plants, precision machines or works of art. Doing so may degrade the quality of the items.
 - Do not use these air conditioners for air-conditioning applications in vehicles or ships. Doing so may cause water and/or power leakages.

Precautions for using air conditioners

Concerning the air conditioner's operating conditions and their selection

(1) Avoid using the air conditioner in the following locations.

- Locations with acidic or alkaline atmospheres (locations at which highly acidic or alkaline air is directly drawn in, such as in hot springs areas from which sulfur gases are given off, or where chemicals, vinegar, exhaust air from burners, etc., are given off) The heat exchangers and other parts may become corroded.
- Locations with atmospheres filled with coolant or other machine oil or steam exhaust (such as at food preparation factories or machine plants). The heat exchangers may corrode; frost may form as a result of heat exchanger malfunction; air conditioner operating performance may be compromised or condensation may form as a result of clogged filters; plastic parts may incur damage; heat-insulation materials may become separated, etc.

Before using an air conditioner in any of the following locations, consult with your dealer or a qualified contractor.

- Locations where vapors from edible oils are given off (such as in bakeries or kitchens and restaurants that use edible oils) ...The air conditioner's operating performance may be compromised or condensation may form as a result of clogged filters, and the plastic parts may incur damage. In line with the prevailing conditions, take countermeasures such as tailoring the installation conditions in accordance with the conditions, using air conditioners designed for kitchens or oil guard filters, etc.
- Locations with disinfectant-induced chlorine atmospheres (water tanks, etc.) The metal parts in the heat exchangers, motors, etc., may become corroded.
- Locations with high salinity (coastal areas, etc.) Corrosion may occur so use outdoor units specifically designed to withstand exposure to salt.

- Locations where power is supplied from independent power generators. The power line frequency and/or voltage may fluctuate, possibly causing the air conditioner to malfunction.
- Locations where high frequencies or electrical noise is generated (from high-frequency welders used for vinyl welding and processing, high-frequency therapeutic devices used for thermotherapy, etc.) The electronic components may be adversely affected, possibly causing the air conditioner to malfunction.
- Locations where electronic equipment is installed. Electrical noise may adversely affect the operation of the electronic equipment.

(3) Concerning use in locations with high ceilings

- In locations with high ceilings, use of circulators for improving the temperature distribution during heating is recommended.

(4) Concerning use in high-humidity environments

- When the ceiling-recessed type of indoor unit is installed in a location, such as those described below, and it is very hot and humid inside the ceiling, condensation may form on the external surfaces of the indoor unit and drip down. In such cases, add external heat-insulating materials.
 - Locations such as food preparation sites in which the areas above the ceilings are hot and humid
 - Locations in which outside air is drawn in and routed above the ceiling
 - Above ceilings with a slate roof or tiled roof overhead

(5) Even when an air conditioner is shut down, it will still consume a small amount of power to protect the unit. If the air conditioner will not be used for a prolonged period, turn OFF the main switch (ground fault circuit breaker). However, before the unit is to be used again, turn ON the main switch (ground fault circuit breaker) for at least 12 hours in order to prevent trouble.



TOSHIBA

TOSHIBA

SMMS
SUPER MODULAR MULTI SYSTEM



ISO
9001
Quality
Management

ISO
14001
Environmental
Management

OHSAS
18001
Occupational
Health & Safety
Management



The First VRF
FOR
Tropical Climate

Notice : Toshiba is committed to continuously improving its products to ensure the highest quality and reliability standards, and to meet local regulations and market requirements All features and specifications are subject to change without prior notice

DEALER

PT BERCA CARRIER INDONESIA

Head Office:

Gedung Pusat Niaga 4th Floor
Arena PRJ Kemayoran
Jakarta 10620, Indonesia
Telp. (62) 21 2664 5888

Service, Spare Parts & Training Center:

Jalan Agung Timur II
Blok O-1, No.40-41 Sunter
Jakarta 14350, Indonesia
Telp. (62) 21 2660 8088